



DS-1212PET Double Sided Polyester Tape

Production Description

ACT DS-1212PET Double Sided Polyester Tape use polyester film as carrier, and coated with excellent and extremely aggressive acrylic adhesive, protected by easy release double-sided release liner.

Features

- ◆ Extremely Aggressive Adhesive
- ◆ Good Initial Tack
- ◆ Excellent Peel Adhesion
- ◆ Good Permanent Bonding

Applications

- 1) Poly bags and envelopes sealing
- 2) Photos, posters, public notes sticking
- 3) Daily life usages
- 4) Paper related products connecting and bonding

Technical Data Sheet

Property	Unit	Value	Test Method
Total Thickness	Micron	90	PSTC-33 / ASTM D3652
Peel Adhesion	N/25mm	18	PSTC-1 / ASTM D3330
Tack Rolling Ball	cm	10	PSTC-6 / ASTM D3121
Tensile Strength	N/25mm	75	PSTC-31 / ASTM D3759
Elongation	%	100	PSTC-31 / ASTM D3759
Service Temperature	°C	-20 ~ +100	-----
Applying Temperature	°C	+10 ~ +40	-----

Jumbo Roll: 1040mm x 1000M; 1240mm x 1000M.

Remarks:

1. The data above are typical results and subject to change without notice.
2. Tolerance: Weight and Thickness: $\pm 10\%$; Width: $\pm 3\text{mm}$; Length: Cut Roll: $\pm 0.3\text{m}$, Jumbo Roll $\pm 0.5\%$.
3. The product should be stored at room temperature and kept from wet and heat source.
Shelf life: One year from shipment date when stored at 21°C (70°F) / 50% relative humidity out of direct sunlight.
4. It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil.
5. The user should take test and do trial-application on the above products before coming into application so as to witness and ensure suitability for user's special purpose and technique.