



# Technical Data Sheet

Product Name: ACT 7110C

## Acrylic Foam Tape

Description	Unit	Value	Test Method
Adhesive		Acrylic	
Carrier		Acrylic Foam	
Color		Clear	
Thickness	mm	1.0 ±50 µm	ASTM-1000
Release Liner		Red PE	
Standard Roll Width	mm	800	
Standard Roll Length	M	33	
<b>Tensile Strength</b>			
To Aluminum (Room Temperature)	gf/cm <sup>2</sup>	≥ 6500	ASTM D-897
<b>180° Peel Adhesion</b>			
To Stainless Steel (Room Temperature)	gf/cm <sup>2</sup>	≥ 4000	ASTM D-3330
<b>Holding Power</b>			
To Stainless Steel (80°C Temperature / 1000g Static Load)	HR	> 24	ASTM D-3654
<b>Dynamic Shear Strength</b>			
To Stainless Steel (Room Temperature <b>after 20 minutes</b> )	gf/cm <sup>2</sup>	≥ 3000	ASTM D-1002
To Stainless Steel (Room Temperature <b>after 24 hours</b> )	gf/cm <sup>2</sup>	≥ 4500	
<b>Temperature Resistance</b>			
<b>Short term</b> (4 hrs conditioning @ indicated temp with 100g static load)	° C	≥ 160	
<b>Long term</b> (Maximum temperature where tape supports 250g in static shear for 10,000 minutes)	° C	≥ 120	

All data is typical and not to be considered specific values. ACT cannot predict or control the different conditions under which this information and our products may be applied. Each user of these products, or information, should perform their own tests to determine the safety, fitness, and suitability of the products, or combination of products, for any foreseeable purposes, applications and uses by the user and by any third party to which the user may convey the products. ACT does not guarantee that the user will obtain the same results as published in this document. The data and information is provided as a technical service, and the data and information are subject to change without notice.