



A. Plan Set Notes

a. General

- 1.** ALL MATERIALS AND WORKMANSHIP SHALL BE IN CONFORMANCE WITH THE CURRENT STANDARDS AND SPECIFICATIONS OF THE APPROPRIATE GOVERNING AGENCY. THE CONTRACTOR SHALL HAVE IN HIS POSSESSION AT ALL TIMES ONE SIGNED COPY OF THE PLANS AND THE STANDARDS, AND SPECIFICATIONS AS APPROVED BY THE APPROPRIATE GOVERNING AGENCY. THE CONTRACTOR SHALL OBTAIN WRITTEN APPROVAL FOR ANY VARIANCE TO THE ABOVE DOCUMENTS.
- 2.** CONTRACTOR SHALL OBTAIN, AT HIS OWN EXPENSE, ALL APPLICABLE CODES, LICENSES, STANDARDS, SPECIFICATIONS, PERMITS, BONDS, ETC. WHICH ARE NECESSARY TO PERFORM THE PROPOSED WORK.
- 3.** IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO NOTIFY THE OWNER/DEVELOPER AND ENGINEER OF ANY PROBLEM IN CONFORMING TO THE APPROVED PLANS FOR ANY ELEMENT OF THE PROPOSED IMPROVEMENTS PRIOR TO ITS CONSTRUCTION.
- 4.** THE CONTRACTOR SHALL BE RESPONSIBLE FOR NOTIFYING THE APPROPRIATE GOVERNING AGENCIES AT LEAST 48 HOURS PRIOR TO START OF ANY CONSTRUCTION. IF WORK IS SUSPENDED FOR ANY PERIOD OF TIME AFTER INITIAL START-UP, THE CONTRACTOR SHALL NOTIFY THE APPROPRIATE AGENCIES 48 HOURS PRIOR TO RESTART.
- 5.** THE CONTRACTOR SHALL BE RESPONSIBLE FOR NOTIFYING THE APPROPRIATE FIRE DEPARTMENT OF ALL STREET CLOSING AND EXISTING FIRE HYDRANTS TAKEN OUT OF SERVICE AT LEAST 48 HOURS PRIOR TO THE START OF CONSTRUCTION.
- 6.** THE CONTRACTOR SHALL NOTIFY ALL PUBLIC UTILITY COMPANIES AND DETERMINE THE LOCATION OF ALL EXISTING UNDERGROUND UTILITIES PRIOR TO PROCEEDING WITH CONSTRUCTION. ALL WORK PERFORMED IN THE AREA OF PUBLIC UTILITIES SHALL BE PERFORMED ACCORDING TO THE REQUIREMENTS OF THESE AGENCIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATING ANY EXISTING UTILITY (INCLUDING DEPTH) WHICH MAY CONFLICT WITH THE PROPOSED CONSTRUCTION. THE CONTRACTOR SHALL PROTECT, AT HIS OWN EXPENSE, ALL EXISTING UTILITIES AND BE RESPONSIBLE FOR THEIR REPAIR IF THEY ARE DAMAGED DURING CONSTRUCTION. ALL KNOWN EXISTING UTILITIES ARE SHOWN IN APPROXIMATE LOCATIONS ON THE PLANS. THE ACTUAL LOCATION MAY VARY FROM THE PLANS, ESPECIALLY IN THE CASE OF UNDERGROUND UTILITIES. WHENEVER CONTRACTOR DISCOVERS A DISCREPANCY IN LOCATIONS HE SHALL CONTACT THE ENGINEER IMMEDIATELY.
- 7.** ANY CONSTRUCTION DEBRIS OR MUD TRACKED ONTO EXISTING ROADWAYS SHALL BE REMOVED IMMEDIATELY BY THE CONTRACTOR. THE CONTRACTOR SHALL REPAIR ANY EXCAVATIONS OR PAVEMENT FAILURES CAUSED BY HIS CONSTRUCTION.

- 8.** PRIOR TO BEGINNING THE WORK, THE CONTRACTOR SHALL OBTAIN ANY WRITTEN AGREEMENTS FOR INGRESS AND EGRESS TO THE WORK FROM ADJACENT PRIVATE PROPERTY IF NEEDED AND SUCH ACCESS SHALL BE MAINTAINED THROUGHOUT THE CONSTRUCTION PERIOD.
- 9.** THE CONTRACTOR SHALL BE SOLELY AND COMPLETELY RESPONSIBLE FOR CONDITIONS AT AND ADJACENT TO THE JOB SITE, INCLUDING SAFETY OF ALL PERSONS AND PROPERTY DURING PERFORMANCE OF THE WORK. THE CONTRACTOR SHALL PROVIDE ALL LIGHTS, SIGNS, BARRICADES, FLAGMEN, OR OTHER DEVICES NECESSARY TO PROVIDE FOR PUBLIC SAFETY. THIS REQUIREMENT SHALL APPLY CONTINUOUSLY AND NOT BE LIMITED TO NORMAL WORKING HOURS.
- 10.** ALL EXCAVATIONS SHALL MEET CURRENT OSHA GUIDELINES AND BE IN CONFORMANCE WITH THE SOILS ENGINEER'S RECOMMENDATIONS. ALL EXCAVATION IS UNCLASSIFIED.
- 11.** THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE REMOVAL AND REPLACEMENT OF ALL MATERIALS DISTURBED WITHIN DEDICATED RIGHT- OF- WAYS AND ALL MATERIALS AND WORKMANSHIP SHALL MEET THE CONSTRUCTION STANDARDS OF THE APPROPRIATE GOVERNING AGENCY.
- 12.** THE CONTRACTOR WILL BE HELD RESPONSIBLE FOR THE PROPER FUNCTIONING OF THE IMPROVEMENTS FOR A MINIMUM OF ONE OR TWO YEARS FROM THE DATE OF ACCEPTANCE OF THE IMPROVEMENTS BY THE APPROPRIATE GOVERNING AGENCY. ANY FAILURE DURING THIS PERIOD OF GUARANTEE SHALL BE REMEDIED BY THE CONTRACTOR TO THE SATISFACTION OF THE APPROPRIATE GOVERNING AGENCY AT NO EXPENSE TO THE AGENCY.
- 13.** THE OWNER SHALL, AT HIS EXPENSE, PROVIDE ONE SET OF CONSTRUCTION STAKES. THE CONTRACTOR SHALL PRESERVE THE STAKES FOR HIS USE. ANY CONSTRUCTION STAKING WHICH IS QUESTIONABLE AS TO CORRECTNESS SHALL BE LEFT IN PLACE UNTIL SUCH TIME AS THE OWNER CAN VERIFY THE CORRECTNESS OF SAID STAKING. SHOULD THE STAKES BE FOUND CORRECT, THE COSTS FOR CHECKING SHALL BE AT THE CONTRACTOR'S EXPENSE. IF CONSTRUCTION STAKING IS OBLITERATED, DESTROYED, OR OTHERWISE RENDERED USELESS DUE TO NEGLIGENCE OR CARELESSNESS BY THE CONTRACTOR OR HIS EMPLOYEES, SAID STAKING SHALL BE REPLACED OR CORRECTED AT THE CONTRACTOR'S EXPENSE.
- 14.** COMPACTION TESTING SHALL BE PROVIDED BY THE CONTRACTOR. IF RETESTING IS REQUIRED DUE TO FAILURES, THE COST OF RETESTING SHALL BE AT THE CONTRACTOR'S EXPENSE.
- 15.** THE CONTRACTOR SHALL KEEP ACCESS OPEN TO ALL PROPERTIES ADJACENT TO THE SITE.
- 16.** WATER SHALL BE USED AS A DUST PALLATIVE WHERE REQUIRED. LOCATIONS SHALL BE AS ORDERED. COST ASSOCIATED WITH DUST CONTROL IS CONSIDERED INCIDENTAL TO THE WORK.

- 17.** ALL PIPE DEFLECTIONS REQUIRE HIGH DEFLECTION COUPLINGS OR APPROVED FITTINGS. BENDS IN THE BARREL OF THE PIPE SHALL NOT BE ALLOWED.
- 18.** BEFORE STARTING ANY CONSTRUCTION, THE CONTRACTOR SHALL LOCATE ANY AND ALL UNDERGROUND FACILITIES/UTILITIES WHICH MAY BE AFFECTED BY THIS PROJECT.
- 19.** REFER TO RECORDED PLAT FOR GEOMETRY.

b. Water System

1. ALL MATERIALS AND WORKMANSHIP SHALL BE IN CONFORMANCE WITH THE MERIDIAN METROPOLITAN DISTRICT (MMD) STANDARDS, MATERIALS, SPECIFICATIONS AND STANDARD DRAWINGS. ALL WORK SHALL BE INSPECTED AND APPROVED BY THE DISTRICT ENGINEER. THE CONTRACTOR SHALL NOTIFY THE DISTRICT ENGINEER AND MERIDIAN METROPOLITAN DISTRICT AT LEAST 48 HOURS PRIOR TO BEGINNING CONSTRUCTION.

2. ALL WATER MAINS INSTALLED SHALL CONFORM TO MERIDIAN METROPOLITAN DISTRICT MATERIALS SPECIFICATIONS:

DUCTILE IRON -	4" & 20" CLASS 51
	MS - 1 6" THROUGH 16" CLASS 50/ WITH POLY WRAP

POLYVINYL CHLORIDE (PVC) BLUE BRUT	4" CLASS 200
	MS - 2 6" THROUGH 12" CLASS 150

3. ALL PIPES SHALL HAVE A TRACER WIRE ATTACHED DURING CONSTRUCTION TO THE TOP OF EVERY LENGTH OF INSTALLED PIPE. THE TRACER WIRE SHALL BE MULTI-STRAND 12 GAUGE COPPER WIRE, AND SHALL BE PERMANENTLY AFFIXED TO THE TOP OF THE PIPE USING NYLON PIPE STRAPS AT 50 FOOT INTERVALS. THE TRACER WIRE SHALL ALSO BE PERMANENTLY CONNECTED TO ALL FIRE HYDRANT TEES, METALLIC PIPE BENDS, MAIN VALVES OR OTHER METALLIC FITTINGS, WITH SUCH CONNECTION NOT INTERFERING WITH CONDUCTIVITY OF THE TRACER WIRE. ALL POINTS OF CONNECTION SHALL BE PROTECTED FROM CORROSION BY AN EPOXY OR SILICONE COATING. TRACER WIRE SHALL TERMINATE AT A TEST PORT (TEST STATION) LOCATED AT EACH PROPOSED FIRE HYDRANT. SPLICES TO WIRE WILL REQUIRE THE USE OF 3M SPLICE KITS. ALSO INSTALL 6 INCH WIDE DETECTABLE ALUMINUM FOIL PLASTIC BACKED TAPE INDICATING BURIED WATER LINE BELLOW. INSTALL 12 TO 18 INCHES BELOW SURFACE GRADE. TAPE MUST BE BLUE IN COLOR AND BE MANUFACTURED BY THORTEC OR EQUAL.

4. ALL FITTINGS SHALL BE MADE FROM GRAY-IRON OR DUCTILE IRON AND FURNISHED WITH MECHANICAL JOINT ENDS. ALL FITTINGS SHALL HAVE A PRESSURE RATING OF 250 PSI AND SHALL BE WRAPPED WITH AN 8-MIL MINIMUM THICKNESS POLYETHYLENE MATERIAL PER AWWA STANDARD C105 (MS-3).

5. THERE SHALL BE A MINIMUM COVER OF 5 FEET OVER ALL WATER MAINS UNLESS INDICATED OTHERWISE ON THESE PLANS.

6. FIRE HYDRANTS SHALL BE WATEROUS PACER 150 OR MUELLER CENTURION, OPEN LEFT, AND THE THREADED HOSE CONNECTIONS SHALL BE 2 ½" NOMINAL DIAMETER WITH 4½ THREADS PER INCH ON THE STEAMER NOZZLE, IN COMPLIANCE WITH SOUTH METRO FIRE PROTECTION DISTRICT REQUIREMENTS. FIRE HYDRANT ASSEMBLIES SHALL INCLUDE ALL PIPE, FITTINGS, OPEN RIGHTVALVES, AND MATERIALS NECESSARY TO INSTALL THE HYDRANT COMPLETE AND IN PLACE.

- 7.** ALL FIRE HYDRANTS ARE TO BE PAINTED DIAMOND VOGEL, MERIDIAN METROPOLITAN DISTRICT GREY, USING AMERCOAT 220 WATERBORNE ACRYLIC, AMERCOAT 220 DEEP TINT 3349710 BTL 408416-334-970.
- 8.** ALL BENDS, TEES, FIRE HYDRANTS, BLOW-OFFS AND PLUGS AT DEAD END MAINS SHALL BE PROTECTED FROM THRUST BY USING CONCRETE THRUST BLOCKS PER MERIDIAN METROPOLITAN DISTRICT STANDARDS.
- 9.** NOT MORE THEN ONE CONNECTION SHALL BE MADE TO EXISTING MAINS UNTIL ALL TESTING IS COMPLETE AND PASSING.
- 10.** CHLORINATION AND FLUSHING: ALL WATER MAINS SHALL BE INSTALLED AND CHLORINATED PER MERIDIAN METROPOLITAN DISTRICT STANDARDS. THE LINES SHALL BE CHLORINATED IN ACCORDANCE WITH AWWA C-651. "DISINFECTING WATER MAINS." THE PREFERRED METHOD IS TO USE SUFFICIENT CHLORINE TABLETS TO PRODUCE A 25 MG/L SOLUTION. THESE TABLETS SHOULD BE ADHERED TO THE TOP OF THE PIPE SECTION WITH PERMATEX CLEAR R.T.V. CHLORINATION OF 16-INCH AND LARGER PIPE REQUIRES A CHLORINE SLURRY. THE CHLORINATION OF ANY FINISHED PIPELINE SHALL BE DONE PRIOR TO HYDROSTATIC TESTING.
- 11.** HYDROSTATIC TESTING: ALL WATER MAINS SHALL BE TESTED PER THE REQUIREMENTS OF MERIDIAN METROPOLITAN DISTRICT STANDARDS. ALL WATER MAIN PIPE SHALL BE FIELD PRESSURE TESTED TO A MINIMUM OF 150 PSI. ALL TESTING SHALL BE DONE IN THE PRESENCE OF THE MERIDIAN METROPOLITAN DISTRICT ENGINEER. ALLOWABLE LEAKAGE FOR EACH SECTION OF PIPE BETWEEN LINE VALVES SHALL NOT EXCEED THE LEAKAGE RATE SET FORTH BELOW,

PIPE SIZE (INSIDE DIAMETER)	ALLOWABLE LEAKAGE PER 1,000 FEET (GAL/HR)	
	DUCTILE IRON PIPE (D.I.P.)	POLYVINYL CHLORIDE (P.V.C.)
4 INCHES	0.37	0.33
6 INCHES	0.55	0.50
8 INCHES	0.74	0.66
12 INCHES	1.10	1.00
16 INCHES	1.47	
20 INCHES	1.84	

- 12.** ALL VALVES SHALL BE OPEN RIGHT AND ARE TO BE LOCATED ON PROPERTY LINE EXTENSIONS EXCEPT FOR TAPPING TEES WHERE AN ADDITIONAL VALVE SHALL BE PLACED ON THE TAPPING TEE. OTHER VALVE LOCATIONS MAY BE REQUIRED AS SHOWN ON THE PLANS.
- 13.** WHEN IT IS NECESSARY TO LOWER OR RAISE WATER LINES AT STORM DRAINS AND OTHER UTILITY CROSSINGS, A MINIMUM CLEARANCE OF 1.5 FEET (18 INCHES) SHALL BE MAINTAINED BETWEEN THE OUTSIDE OF PIPES.

- 14.** THE CONTRACTOR SHALL HAVE IN HIS POSSESSION AT ALL TIMES ONE (1) SIGNED COPY OF THE APPROVED PLANS.
- 15.** COMPACTION OF ALL TRENCHES MUST BE ATTAINED BY THE CONTRACTOR AND THE COMPACTION TEST RESULTS SUBMITTED TO THE DISTRICT ENGINEER.
- 16.** ALL BENDS SHALL BE RESTRAINED PER THE RESTRAINING TABLE.
- 17.** METER LOCATIONS SHALL BE DETERMINED AND APPROVED BY THE DISTRICT ENGINEER. IT IS THE DEVELOPERS RESPONSIBILITY TO CONTACT THE MERIDIAN METROPOLITAN DISTRICT AT 303-790-0345.
- 18.** THE CONTRACTOR SHALL CONFORM TO ALL FEDERAL, STATE AND LOCAL HEALTH AND SAFETY RULE AND REGULATIONS. ALL TRENCHES SHALL BE OPEN CUT FROM THE GROUND SURFACE AND SHALL CONFORM TO THE MERIDIAN METROPOLITAN DISTRICT STANDARDS, TYPICAL TRENCH SECTION. ALL TRENCHES SHALL BE OPEN CUT FROM GROUND SURFACE AND SHALL NOT EXCEED A WIDTH OF 48-INCHES AT A POINT 12-INCHES ABOVE THE CROWN OF THE PIPE. ALL TRENCHES SHALL BE PROPERLY BRACED AND/OR SHORED IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL OCCUPATIONAL SAFETY AND HEALTH (OSHA) REQUIREMENTS. SHORING SHALL BE REMOVED AS THE WORK AND BACKFILLING OPERATIONS PROGRESS.
- 19.** THE DISCHARGE FROM ANY TRENCH DEWATERING OPERATIONS SHALL BE DISCHARGED INTO NATURAL DRAINAGE CHANNELS OR OTHER STRUCTURES AS APPROVED BY THE ENGINEER. BY NO MEANS SHALL GROUND WATER BE ALLOWED TO BE DISCHARGED INTO THE SANITARY SEWER SYSTEMS.

PIPE TRENCHES SHALL BE KEPT FREE FROM WATER DURING EXCAVATION, FINE GRADING, PIPE LAYING AND JOINTING. DEWATERING SUFFICIENT TO PROVIDE A COMPLETELY DRY TRENCH SHALL BE MAINTAINED DURING ALL PIPE LAYING AND JOINTING OPERATIONS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DAMAGE OF ANY NATURE RESULTING FROM THE DEWATERING OPERATIONS.
- 20.** BEDDING CONFORMING TO THE MERIDIAN METROPOLITAN DISTRICT REQUIREMENTS SHALL BE USED THROUGHOUT THE PROJECT (BEDDING SHALL BE PLACED 6" MINIMUM AROUND AND BELOW THE PIPE AND 12" MINIMUM ABOVE THE PIPE).
- 21.** EXCAVATED MATERIALS SHALL NORMALLY BE CONSIDERED SUITABLE FOR BACKFILL UNLESS ANOMALOUS CONDITIONS ARE DISCOVERED DURING EXCAVATION. NO RUBBISH, DEBRIS, ORGANIC MATERIALS, RUBBLE AND STONES LARGER THAN 3 INCHES IN DIAMETER SHALL BE USED IN THE BACKFILL. CLAYS WITH A PLASTICITY INDEX IN EXCESS OF 20 SHALL NOT BE USED FOR BACKFILL IN TRENCHES LOCATED IN APPROVED STREETS. BACKFILL (ABOVE BEDDING MATERIAL) WITHIN STREET RIGHT-OF-WAY OR UNDER PAVEMENT SHALL BE COMPACTED TO A MINIMUM DENSITY OF 95% STANDARD PROCTOR AS DETERMINED BY AASHTO METHOD T-99. BACKFILL NOT IN STREET RIGHT-OF-WAY OR UNDER PAVEMENT SHALL BE COMPACTED TO A STANDARD PROCTOR DENSITY TO THAT OF THE UNDISTURBED NATURAL GROUND BEFORE CONSTRUCTION.

22. ONLY THE FOLLOWING FIRE HYDRANTS, VALVE BOXES AND JOINT RESTRAINTS LISTED BELOW SHALL BE ACCEPTED FOR CONSTRUCTION:

FIRE HYDRANTS:

WATEROUS PACER 150 OR MUELLER CENTURION (SEE NOTES 6 & 7)

VALVE BOXES:

TYLER SCREW - TYPE "C" CAST IRON VALVE BOX ASSEMBLY - SERIES 6860 WITH NO. 160 OVAL BASE

MECHANICAL JOINT RESTRAINT DEVICES SHALL BE:

FOR DUCTILE IRON PIPE (DIP):

MEGALUG 1100 SERIES
UNI-FLANGE 1400 SERIES

POLYVINYLCHLORIDE (PVC) PIPE:

MEGALUG 2000 PV SERIES
UNI-FLANGE 1500 SERIES

PIPE JOINT RESTRAINT DEVICES SHALL BE:

FOR DUCTILE IRON PIPE (DIP):

MEGALUG 1700 SERIES
UNI-FLANGE 1300 SERIES

POLYVINYLE CHLORIDE (PVC) PIPE:

MEGALUG 1500 SERIES
UNI-FLANGE 1300 SERIES

- 23.** ALL WATER MAIN VALVES SHALL BE OPEN RIGHT (RED TOP), AND THE PLANS SHOULD INDICATE THIS AT EACH VALVE LOCATION.
- 24.** EXISTING VALVES IN THE DISTRICT MAY ONLY BE OPERATED BY THE MERIDIAN METROPOLITAN DISTRICT PERSONNEL, (303-790-0345).
- 25.** PRIOR TO INSTALLATION OF WATER MAINS, ROAD CONSTRUCTION MUST HAVE PROGRESSED TO AT LEAST THE "SUB-GRADE" STATE. SUB-GRADE IS DEFINED AND AN ELEVATION OF NO MORE THEN SEVEN (7) INCHES BELOW THE FINISHED STREET GRADE.
- 26.** ALL VALVE BOXES AND HYDRANTS WILL BE SET TO THE FINAL FINISHED GRADE BY THE CONTRACTOR. ANY VALVE BOXES IN NON-PAVED LOCAIONS SHALL BE MARKED WITH A MARKER POST PER THE DISTRICT'S SPECIFICATIONS.
- 27.** BEFORE ANY TAPS ARE MADE, APPLICATION FOR SAID TAPS MUST BE RECEIVED AND APPROVED BY THE MERIDIAN METROPOLITAN DISTRICT.
- 28.** ALL POLYVINYL CHLORIDE (PVC) PIPE IS TO BE DEPRESSURIZED PRIOR TO TAPPING.

29. ALL WATER MAIN AND APPURTENANCES ARE TO BE CLEARLY STAKED WITH OFFSET STAKES PRIOR TO INSPECTION. TO ASSURE PROPER PLACEMENT OF PIPE, ANY AND ALL WATER EASEMENTS SHALL BE CLEARLY IDENTIFIED AS WELL.

30. "AS-BUILT" MYLAR DRAWINGS ARE TO BE REPRODUCIBLE COPIES 24"X 36" SIZE OF THE APPROVED CONSTRUCTION DRAWINGS. ANY FIELD CHANGES ARE TO BE NOTED. THE DRAWING(S) WILL STATE "AS-BUILT" IN LARGE BLOCK LETTERS. A PRINT OF THE MYLAR IS TO BE SIGNED, DATED AND STAMPED BY THE REGISTERED ENGINEER OR THE "AS-BUILT" PRINT MAY BE STAMPED AND SIGNED BY A COLORADO-REGISTERED PROFESSIONAL LAND SURVEYOR INSTEAD OF, OR IN ADDITION TO, A REGISTERED ENGINEER. THE SURVEYOR'S CERTIFICATION IS FOR SURVEY DATA ONLY AND A NOTE TO THIS EFFECT SHOULD BE INCLUDED BY THE LS SEAL.

"AS-BUILT" FIELD NOTES, FROM WHICH THE "AS-BUILT" DRAWINGS ARE PREPARED, ARE TO BE PROVIDED AND STAMPED / SIGNED AND DATED BY THE REGISTERED LAND SURVEYOR.

31. THE DEVELOPER SHALL BE RESPONSIBLE FOR OBTAINING THE FOLLOWING:

- A. PROVIDE THE DISTRICT ENGINEERS A DEVELOPER'S WARRANTY, INCLUDING LIEN WAVERS AND ALL OTHER ASSURANCES THAT PAYMENT OF ALL SUPPLIES OF LABOR AND/OR MATERIAL HAS OCCURRED.
- B. PROVIDE THE DISTRICT ENGINEERS A BILL OF SALE, INCLUDING A DESCRIPTION OF THE FACILITIES.

32. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING AND PAYING FOR THE FOLLOWING:

- A. SUPPLYING THE DISTRICT ENGINEER WITH AN "ENGINEERS ESTIMATE" OF ALL COSTS ASSOCIATED WITH THE WATER INSTALLATION, PRIOR TO CONSTRUCTION.
- B. STREET CUTTING PERMITS FROM THE APPROPRIATE AUTHORITIES.
- C. RESTORATION OF DISTURBED STREET PAVEMENT AS REQUIRED BY GOVERNING AUTHORITIES.
- D. ALL COSTS ASSOCIATED WITH INSPECTION BY THE APPOINTED REPRESENTATIVES OF GOVERNING AUTHORITIES.
- E. TESTING OF COMPLETED WATER LINES AS REQUIRED BY APPOINTED REPRESENTATIVE OF THE MERIDIAN METROPOLITAN DISTRICT.

- F. COORDINATING WITH THE DISTRICT ENGINEER ANY AND ALL WATER OUTAGES NECESSARY FOR CONSTRUCTION WELL IN ADVANCE IN ORDER TO ALLEVIATE ANY UNEXPECTED OUTAGES, AND ALLOW THE DISTRICT MAINTENANCE CREWS TIME TO LOCATE AND OPERATE SAID VALVES.
 - G. A PERFORMANCE AND PAYMENT BOND GUARANTEEING PAYMENT BY THE CONTRACTOR OF ALL BILLS BEFORE FINAL PAYMENT UNDER THIS CONTRACT.
 - H. VERIFICATION OF ALL OTHER UNDERGROUND FACILITIES WHICH MAY BE AFFECTED BY THIS PROJECT AND REPAIR THEREOF IN CASE OF DAMAGE.
 - I. SCHEDULE A PRE-CONSTRUCTION MEETING TO INCLUDE AT LEAST THE CONTRACTOR, ENGINEER, OWNER OR OWNER'S REPRESENTATIVE, AND A REPRESENTATIVE FROM THE MERIDIAN METROPOLITAN DISTRICT. THE CONTRACTOR SHALL GIVE AT LEAST 48-HOURS NOTICE TO THE ATTENDEES PRIOR TO THE PRE-CONSTRUCTION MEETING AND PRIOR TO COMMENCING CONSTRUCTION.
 - J. "AS-CONSTRUCTED" MYLARS, ELECTRONIC FILES, FIELD NOTES AND CUT-SHEETS SHALL BE SUPPLIED TO THE DISTRICT ENGINEER PRIOR TO CONDITIONAL ACCEPTANCE OF THE WATER LINES.
- 33.** A BACKFLOW PREVENTION ASSEMBLY APPROVED BY THE MERIDIAN METROPOLITAN DISTRICT IS REQUIRED ON ALL COMMERCIAL AND MULTI-FAMILY DOMESTIC TAPS.
- 35.** ALL COMBINATION FIRE-LINE AND DOMESTIC TAPS MUST BE INSPECTED AND APPROVED BY THE DISTRICT ENGINEER PRIOR TO THE RELEASE OF THE WATER MAINS
- 36.** THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SAFETY OF ALL PERSONNEL(S) ASSOCIATED WITH THIS PROJECT AND THE GENERAL PUBLIC WHERE THE PROJECT IS ON PUBLIC RIGHT-OF-WAY.
- 37.** SAFETY/CONSTRUCTION FENCING MUST BE PLACED ENTIRELY AROUND ANY OPEN EXCAVATION AT THE END OF EACH DAY.
- 38.** OBSERVATION OF CONSTRUCTION/WORK IN PROGRESS AND ON-SITE VISITS ARE NOT TO BE CONSTRUED AS A GUARANTEE BY THE DISTRICT OR DISTRICT ENGINEER, OF CONTRACTORS PERFORMANCE, OR OBLIGATIONS TO THE COMPLIANCE OF THE CONTRACT.
- 39.** MERIDIAN METROPOLITAN DISTRICT PERSONNEL ARE NOT RESPONSIBLE FOR SAFETY IN, ON, OR ABOUT THE PROJECT SITE, NOR FOR THE COMPLIANCE BY THE APPROPRIATE PARTY OF ANY REGULATION RELATING THERETO. ALL SAFETY COMPLIANCE/ENFORCEMENT AT THE WORK SITE SHALL BE THE CONTRACTOR'S RESPONSIBILITY.

IN CASE OF AN EMERGENCY AFTER WORKING HOURS, CALL THE MERIDIAN METROPOLITAN DISTRICT AT 303-790-1498

c. Sanitary Sewer System

1. THE MERIDIAN METROPOLITAN DISTRICT STANDARD CONSTRUCTION SPECIFICATIONS AND DRAWINGS SHALL BE THE MINIMUM REQUIREMENTS FOR THIS PROJECT.
2. PIPE SHALL BE POLYVINYL CHLORIDE (PVC) CONFORMING TO ASTM-3034 SDR-35 WITH ELASTROMERIC GASKETED JOINTS FOR SIZES 15-INCHES AND SMALLER, AND ASTM F-679 (WALL THICKNESS T-1) WITH ELASTROMERIC GASKETED JOINTS FOR SIZES 18-INCHES AND LARGER.
3. THE MAXIMUM DEFLECTION OF PVC PIPE, AFTER INSTALLATION AND BACKFILLING, SHALL NOT EXCEED 5% OF THE PIPE DIAMETER. THE MAXIMUM INDIVIDUAL PIPE LENGTH OF PVC PIPE SHALL BE 20-FEET, 10-FOOT LENGTHS WHERE PIPE IS LAID AT MINIMUM GRADE.
4. ALL DUCTILE IRON PIPE (DIP) SHALL CONFORM TO AWWA C-151 CLASS 51.
5. THE CONTRACTOR SHALL CONFORM TO ALL FEDERAL, STATE AND LOCAL HEALTH AND SAFETY RULES AND REGULATIONS. ALL TRENCHES SHALL BE OPEN CUT FROM GROUND SURFACE AND SHALL NOT EXCEED A WIDTH OF 48-INCHES AT A POINT 12-INCHES ABOVE THE CROWN OF THE PIPE. ALL TRENCHES SHALL BE PROPERLY BRACED AND/OR SHORED IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL OCCUPATIONAL SAFETY AND HEALTH (OSHA) REQUIREMENTS. SHORING SHALL BE REMOVED AS THE WORK AND BACKFILLING OPERATIONS PROGRESS.
6. MERIDIAN METROPOLITAN DISTRICT "CLASS B" BEDDING SHALL BE USED THROUGHOUT THE PROJECT (BEDDING SHALL BE PLACED 6" MINIMUM AROUND AND BELOW THE PIPE AND 12" MINIMUM ABOVE THE PIPE). BEDDING MATERIAL SHALL CONFORM TO ASTM C-33 OR D-448 GRADATION No. 67 OR 6 RESPECTIVELY.
7. EXCAVATED MATERIAL SHALL NORMALLY BE CONSIDERED SUITABLE FOR BACKFILL UNLESS ANOMALOUS CONDITIONS ARE DISCOVERED DURING EXCAVATION. NO RUBBLE AND STONES LARGER THAN 3-INCHES IN DIAMETER, RUBBISH, DEBRIS, OR ORGANIC MATERIALS, SHALL BE USED IN BACKFILL. CLAYS WITH A PLASTICITY INDEX IN EXCESS OF 20 SHALL NOT BE USED FOR BACKFILL IN TRENCHES LOCATED IN APPROVED STREETS. BACKFILL (ABOVE CLASS B MATERIAL) WITHIN STREET AREAS SHALL BE COMPACTED TO A MINIMUM DENSITY OF 95% STANDARD PROCTOR AS DETERMINED BY AASHTO METHOD T-99. BACKFILL NOT UNDER STREETS SHALL BE COMPACTED TO A STANDARD PROCTOR DENSITY EQUAL TO THAT OF THE UNDISTURBED NATURAL GROUND BEFORE CONSTRUCTION.
8. THE DISCHARGE FROM ANY TRENCH DEWATERING OPERATIONS SHALL BE DISCHARGED INTO NATURAL DRAINAGE CHANNELS OR OTHER STRUCTURES AS APPROVED BY THE ENGINEER. BY NO MEANS SHALL GROUND WATER BE ALLOWED TO BE DISCHARGED INTO THE SANITARY SEWER SYSTEMS.

PIPE TRENCHES SHALL BE KEPT FREE FROM WATER DURING EXCAVATION, FINE GRADING, PIPE LAYING AND JOINTING. DEWATERING SUFFICIENT TO PROVIDE A COMPLETELY DRY TRENCH, SHALL BE MAINTAINED DURING ALL PIPE LAYING AND JOINTING OPERATIONS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DAMAGE OF ANY NATURE RESULTING FROM THE DEWATERING OPERATIONS.

9. INFILTRATION AND EX-FILTRATION SHALL NOT EXCEED 100 GALLONS PER INCH OF PIPE DIAMETER PER MILE OF SEWER PER DAY FOR VITRIFIED CLAY PIPE (VCP), AND 50 GALLONS PER INCH OF PIPE DIAMETER PER MILE OF SEWER PER DAY FOR PVC PIPE.

10. EVERY SECTION OF PIPE SHALL BE TELEVISED AND TESTED USING A LOW-PRESSURE AIR TEST.

TESTING OF PVC PIPE LINES SHALL CONFORM TO UNI-BELL PLASTIC PIPE ASSOCIATION'S "RECOMMENDED PRACTICE FOR LOW-PRESSURE AIR TESTING OF INSTALLED SEWER PIPE", UNI-B-6-79.

11. IF LASERS ARE USED TO GIVE LINE AND GRADE FOR THE SEWER LINES, THEY MUST BE CHECKED EVERY 25-FEET FOR THE FIRST 100-FEET AND EVERY 50- FEET THEREAFTER.

12. THE CONTRACTOR SHALL HAVE ONE (1) SET OF PLANS APPROVED BY THE MERIDIAN METROPOLITAN DISTRICT ON SITE AT ALL TIMES.

13. THE CONTRACTOR SHALL NOTIFY THE DISTRICT ENGINEER AT LEAST 48 HOURS PRIOR TO STARTING CONSTRUCTION.

14. COMPACTION TEST RESULTS SHALL BE SUBMITTED TO THE DISTRICT ENGINEER PRIOR TO FINAL ACCEPTANCE.

15. SANITARY SEWER SERVICES SHALL BE WYES OFF OF THE MAIN LINE ON NEW CONSTRUCTION AND WYE SADDLES WITH STAINLESS STEEL STRAPS ON EXISTING MAINS.

16. ALL SANITARY SEWER MAINS AND APPURTENANCES ARE TO BE CLEARLY STAKED WITH OFFSET STAKES PRIOR TO INSPECTION TO ASSURE PROPER PLACEMENT OF PIPE. ANY AND ALL SANITARY SEWER EASEMENTS SHALL BE CLEARLY IDENTIFIED AS WELL.

17. "AS-BUILT" MYLAR DRAWINGS ARE TO BE REPRODUCIBLE COPIES 24"X36" SIZE OF THE APPROVED CONSTRUCTION DRAWINGS. ANY FIELD CHANGES ARE TO BE NOTED. THE DRAWING(S) WILL STATE "AS-BUILT" IN LARGE BLOCK LETTERS. A PRINT OF THE MYLAR IS TO BE SIGNED, DATED AND STAMPED BY THE REGISTERED ENGINEER OR THE "AS-BUILT" PRINT MAY BE STAMPED AND SIGNED BY A COLORADO-REGISTERED PROFESSIONAL LAND SURVEYOR INSTEAD OF, OR IN ADDITION TO, A REGISTERED ENGINEER. THE SURVEYOR'S CERTIFICATION IS FOR SURVEY DATA ONLY AND A NOTE TO THIS EFFECT SHOULD BE INCLUDED BY THE LS SEAL.

"AS-BUILT" FIELD NOTES, FROM WHICH THE "AS-BUILT" DRAWINGS ARE PREPARED, ARE TO BE PROVIDED AND STAMPED / SIGNED AND DATED BY THE REGISTERED LAND SURVEYOR.

18. THE DEVELOPER SHALL BE RESPONSIBLE FOR OBTAINING THE FOLLOWING:

- A. PROVIDE THE DISTRICT ENGINEERS A DEVELOPER'S WARRANTY, INCLUDING LIEN WAVERS AND ALL OTHER ASSURANCES THAT PAYMENT OF ALL SUPPLIES OF LABOR AND/OR MATERIAL HAS OCCURRED.
- B. PROVIDE THE DISTRICT ENGINEERS A BILL OF SALE, INCLUDING A DESCRIPTION OF THE FACILITIES.

19. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING AND PAYING FOR THE FOLLOWING:

- A. SUPPLYING THE DISTRICT ENGINEER WITH AN "ENGINEERS ESTIMATE" OF ALL COSTS ASSOCIATED WITH THE SANITARY SEWER INSTALLATION, PRIOR TO CONSTRUCTION.
- B. STREET CUTTING PERMITS FROM THE APPROPRIATE AUTHORITIES.
- C. RESTORATION OF DISTURBED STREET PAVEMENT AS REQUIRED BY GOVERNING AUTHORITIES.
- D. ALL COSTS ASSOCIATED WITH INSPECTION BY THE APPOINTED REPRESENTATIVE OF THE MERIDIAN METROPOLITAN DISTRICT AND GOVERNING AUTHORITIES.
- E. TESTING OF COMPLETED SANITARY SEWER LINES AS REQUIRED BY APPOINTED REPRESENTATIVE OF THE MERIDIAN METROPOLITAN DISTRICT.
- F. A PERFORMANCE AND PAYMENT BOND GUARANTEEING PAYMENT BY THE CONTRACTOR OF ALL BILLS BEFORE FINAL PAYMENT UNDER THIS CONTRACT.
- G. VERIFICATION OF ALL OTHER UNDERGROUND FACILITIES WHICH MAY BE AFFECTED BY THIS PROJECT AND REPAIR THEREOF IN CASE OF DAMAGE.
- H. SCHEDULE A PRE-CONSTRUCTION MEETING TO INCLUDE AT LEAST THE CONTRACTOR, ENGINEER, OWNER OR OWNER'S REPRESENTATIVE, A REPRESENTATIVE OF THE MERIDIAN METROPOLITAN DISTRICT. THE CONTRACTOR SHALL GIVE AT LEAST 48-HOURS NOTICE TO THE ATTENDEES PRIOR TO THE PRE-CONSTRUCTION MEETING AND PRIOR TO COMMENCING CONSTRUCTION.
- I. JETTING AND TELEVISIONING ALL MAINLINE SANITARY SEWER MAINS UPON COMPLETION.

J. "AS-CONSTRUCTED" MYLARS, ELECTRONIC FILES, FIELD NOTES AND CUT-SHEETS SHALL BE SUPPLIED TO THE MERIDIAN METROPOLITAN DISTRICT PRIOR TO CONDITIONAL ACCEPTANCE OF THE SANITARY SEWER LINES.

20. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SAFETY OF ALL PERSONNEL(S) ASSOCIATED WITH THIS PROJECT AND THE GENERAL PUBLIC WHERE THE PROJECT IS ON PUBLIC RIGHT-OF-WAY.

21. SAFETY/CONSTRUCTION FENCING MUST BE PLACED ENTIRELY AROUND ANY OPEN EXCAVATION AT THE END OF EACH DAY.

22. OBSERVATION OF CONSTRUCTION/WORK IN PROGRESS AND ON-SITE VISITS ARE NOT TO BE CONSTRUED AS A GUARANTEE BY THE DISTRICT OR DISTRICT ENGINEER, OF CONTRACTORS PERFORMANCE, OR OBLIGATIONS TO THE COMPLIANCE OF THE CONTRACT.

23. MERIDIAN METROPOLITAN DISTRICT PERSONNEL ARE NOT RESPONSIBLE FOR SAFETY IN, ON, OR ABOUT THE PROJECT SITE, OR FOR THE COMPLIANCE BY THE APPROPRIATE PARTY OF ANY REGULATION RELATING THERETO. ALL SAFETY COMPLIANCE/ENFORCEMENT AT THE WORK SITE SHALL BE THE CONTRACTOR'S RESPONSIBILITY.

d. Sanitary Sewer Manhole

1. ALL CONCRETE USED IN MANHOLE CONSTRUCTION SHALL DEVELOP 4000 PSI COMPRESSIVE STRENGTH AFTER 28 DAYS. TYPE II CEMENT SHALL BE USED AND AIR ENTRAINMENT IS REQUIRED.
2. ALL MANHOLES SHALL HAVE SEMI-CIRCULAR SHAPED INVERTS FOR SMOOTH FLOW. THE INVERT MAY BE FORMED DIRECTLY IN THE CONCRETE OF THE BASE.
3. PRE-CAST MANHOLE RISERS (BODIES), AND CONES SHALL CONFORM TO ASTM C-478. ALL MANHOLES SHALL HAVE ECCENTRIC CONES (NO FLAT TOPS).
4. ALL JOINTS IN PRE-CAST MANHOLES SHALL BE SEALED WITH A PREFORMED, FLEXIBLE SEALING COMPOUND CONFORMING TO FEDERAL SPECIFICATION SS-S-00210 (GSA-FSS), SUCH AS "RAM-NEK" OR EQUAL AND CEMENT GROUT SHALL BE USED ON ALL OUTSIDE JOINTS WHERE GROUNDWATER IS PRESENT
5. MANHOLE STEPS SHALL BE EXTRUDED ALUMINUM, CONFORMING TO FEDERAL SPECIFICATION QQ-A-200/8, OR POLYPROPYLENE REINFORCED PLASTIC, INSTALLED IN A STRAIGHT LINE VERTICALLY AND SPACED 16-INCHES MAXIMUM APART, STEPS SHALL BE PRE-CAST IN THE MANHOLE WALL.
6. MANHOLE RING AND COVER SHALL BE NOMINAL 24-INCH DIAMETER STANDARD PATTERN CAST IRON.
7. COVER SHALL BE THE DISTRICT STANDARD PATTERN. ALL CAST IRON CASTINGS SHALL BE OF GRAY CAST IRON, ASTM DESIGNATION A48 CLASS 35B. CASTINGS SHALL NOT BE PAINTED OR DIPPED. ALL ALUMINUM CASTINGS SHALL BE DIPPED IN POLYMERIC PAINT AND CONTRACTOR MUST HAVE WRITTEN DISTRICT APPROVAL PRIOR TO INSTALLATION.
8. AN APPROVED MANHOLE WATER STOP GASKET SHALL BE INSTALLED ON ALL PLASTIC PIPE ENTERING A MANHOLE.
9. ALL MANHOLE BASES SHALL BE CAST-IN-PLACE CONCRETE. USE OF PRE-CAST MANHOLE BASES IS NOT PERMITTED, UNLESS APPROVED BY THE DISTRICT ENGINEER.

MERIDIAN METROPOLITAN DISTRICT

UTILITY DETAIL DRAWINGS

November 2012



Meridian Metropolitan District

Utility Detail Drawings

Table of Contents

WATER MAIN

Pipe Bedding.....	WM-1
Valve and Fire Hydrant Location.....	WM-2
Fire Hydrant Assembly.....	WM-3
Tracer Wire Installation.....	WM-4
Wet Tap.....	WM-5
Concrete Thrust Block.....	WM-6
Mechanical Joint Restraint.....	WM-7
Length of Restrained Pipe.....	WM-8
Flange Lug.....	WM-9
Tie-Rod Retaining Clamp.....	WM-10
Restrained Joints at Vertical Bends.....	WM-11
Air Valve Assembly	WM-12
Air Vent Assembly.....	WM-13
Transmission Main Blowoff Installation.....	WM-14
Blowoff Installation for 12” and Smaller Pipe.....	WM-15
Valve Box Detail.....	WM-16
Valve Box Support Plate and Valve Operator Extension Guide.....	WM-17
Valve Operator Extension and Guide.....	WM-18
Zone Valve Manhole.....	WM-19
Pressure Reducing Vault.....	WM-20
Pressure Reducing Vault Notes.....	WM-20A

WATER & IRRIGATION SERVICE

Water and Sewer Service Joint Trench Detail.....	WS-1
Residential Water Service Location.....	WS-2
Water Main Service Connection Detail.....	WS-3
Curb Stop for ¾” and 1” Lines.....	WS-4
Residential Curb Stop Box Location with Attached Sidewalk.....	WS-5
Residential Curb Stop Box Location with Detached Sidewalk.....	WS-6
Standard Water Service Installation.....	WS-7
Service Connection to Existing Stub under Street.....	WS-8

WATER & IRRIGATION SERVICE (CONT.)

Service/Fire or Irrigation Connection	WS-9
Fire main and Domestic Water Service Installation Detail.....	WS-10
Remote Reading ¾" & 1" Meter Typical Inside Setting.....	WS-11
Remote Reading ¾" & 1" Meter Typical Inside Setting (Commercial).....	WS-11A
Inside Setting for 1 ½" and Larger Water Meters with Bypass.....	WS-12
Typical Water Meter Assembly for 1 ½" and 2" Meters.....	WS-13
Typical Water Meter and Backflow Preventer Assembly.....	WS-14
Domestic Standard 3" & 4" Meter & Backflow Assembly Elevation Drawing.....	WS-15
Domestic Standard 3" & 4" Meter & Backflow Assembly Elevation Drawing.....	WS-16
Typical Location for Reduced Pressure Principal Device Backflow Preventer.....	WS-17
Typical Location for a Reduced Pressure Principal Device Backflow Preventer (2 ½" and Larger).....	WS-18
Typical Installation for Reduced Pressure Principal Device Backflow Preventers in Series.....	WS-19
Typical Vertical Backflow Preventer Installation.....	WS-20
Standard Setting for 1 ½" & 2" Domestic Meter Vault.....	WS-21
Domestic Standard 3" & 4" Meter Setting.....	WS-22
Domestic Standard 3" & 4" Meter Vault.....	WS-23
Residential Irrigation System – Pressure Vacuum Breaker.....	WS-24
Irrigation Line, Stop Box and Outside Meter Installation.....	WS-25
Meter Pit for ¾" & 1" Meters.....	WS-26
Outside Setting for 1 ½" & 2" Irrigation Meter in Manhole.....	WS-27
Irrigation Standard 3" & 4" Meter Setting.....	WS-28
Irrigation Standard 3" & 4" Meter Setting.....	WS-29
Meter Setting for Inside or Outside Installation with Custom Setter (1 ½" or 2")... 4" Meter Vault.....	WS-30
8" Meter Vault.....	WS-31
	WS-32

SANITARY SEWER MAIN

Sanitary Sewer Main Bedding Detail.....	SM-1
Sanitary Sewer Main Crossing.....	SM-2
Concrete Encasement Detail.....	SM-3
Standard Manhole Detail.....	SM-4
Pre-Cast Sanitary Manhole Base Detail.....	SM-5
Standard Manhole Base Detail.....	SM-6
Standard Manhole Base Re-Bar Basket.....	SM-7

SANITARY SEWER MAIN (CONT.)

Standard Manhole Base Re-Bar Basket.....	SM-8
Typical Base and Deflector Detail.....	SM-9
Manhole Invert Tie-In Detail.....	SM-10
Manhole Platform Detail.....	SM-11
Inside Drop Manhole Construction Detail.....	SM-12
Standard Step for Manholes.....	SM-13
24" Manhole Cover Detail.....	SM-14
30" Manhole Cover Detail.....	SM-15
Dead End Manhole Service Connection Detail.....	SM-16
Force Main Plug Valve Manhole Detail.....	SM-17

SANITARY SEWER SERVICE

Sanitary Sewer Service Tapping Detail.....	SS-1
Sanitary Service Connection.....	SS-2
Sanitary Sewer Service Location Only.....	SS-3
In-Line Sanitary Sewer Cleanout.....	SS-4
Sand and Oil Interceptor.....	SS-5
Sand and Oil Interceptor.....	SS-6
Grease Interceptor.....	SS-7
Grease Interceptor.....	SS-8
Waster Metering Manhole.....	SS-9
Flume Design Criteria.....	SS-9A
Waste Metering Manhole.....	SS-9B
Waste Metering Manhole.....	SS-9B

STANDARD DETAILS


Bore Casing Detail.....	D-1
Double Bore Casing Detail.....	D-2
Reference Post Typical Detail.....	D-3
Adjustable Support Detail (Standard).....	D-4
Adjustable Support Detail (Heavy Duty).....	D-5
Tidflex Check Valve Detail for Drain Outlet.....	D-6
Concrete Washout Sign.....	D-7
Construction Access Sign.....	D-8

COMMUNICATION DETAILS

Duct Encasement Sections.....	DAS-1
Typical Control Conduit Manhole.....	DAS-2
Control Conduit Typical Street Crossing.....	DAS-3
Control Conduit Pull Box Arrangement.....	DAS-4
Typical Manhole Installation for Control Duct Banks.....	DAS-5

STREET LIGHTING DETAILS

Street Lighting.....	STL-1
Street Lighting.....	STL-2



1. BACKFILL OVER PIPE SHALL BE COMPACTED TO 90% MAXIMUM DRY WEIGHT DENSITY ASHTO T-99
2. PIPE BEDDING SHALL BE SQUEEGEE OR $\frac{3}{4}$ " CRUSHED ROCK.

REV. DATE


August, 2012



MERIDIAN METROPOLITAN DISTRICT

PIPE BEDDING DETAIL

WM-1



REV. DATE


August, 2012



MERIDIAN METROPOLITAN DISTRICT

VALVE AND FIRE HYDRANT LOCATION DETAIL

WM-2



NOTES:

1. HYDRANT SHALL BE WATEROUS PACER 150 OR MUELLER CENTURION, OPEN LEFT, AND THE THREADED HOSE CONNECTIONS SHALL BE 2½" NOMINAL DIAMETER WITH 4½ THREADS PER INCH ON THE STEAMER NOZZLE, IN COMPLIANCE WITH SOUTH METRO FIRE PROTECTION DISTRICT REQUIREMENTS. FIRE HYDRANT ASSEMBLIES SHALL INCLUDE ALL PIPE, FITTINGS OPEN RIGHT VALVES, AND MATERIALS NECESSARY TO INSTALL THE HYDRANT COMPLETE AND IN PLACE.
2. ALL FIRE HYDRANTS ARE TO BE PAINTED DIAMOND VOGEL, MERIDIAN METROPOLITAN DISTRICT GREY, USING AMERCOAT 220 WATERBORNE ACRYLIC, AMERCOAT 220 DEEP TINT 3349710 BTL 408416-334-970.
3. HYDRANT PIT SHALL CONTAIN A MINIMUM OF 1 C.Y. OF ¾" CRUSHED ROCK
4. DISTANCE FROM BACK OF WALK, SEE WM-2.

REV. DATE


August, 2012




MERIDIAN METROPOLITAN DISTRICT

TYPICAL FIRE HYDRANT & ASSEMBLY

WM-3



PROFILE



PLAN

REV. DATE



August, 2012



MERIDIAN METROPOLITAN DISTRICT

TRACER WIRE INSTALLATION DETAIL

WM-4



REV. DATE
August, 2012




MERIDIAN METROPOLITAN DISTRICT

WET TAP


WM-5

ITECHENTER\proj\2008-08-24\img\BLOCCK\BUNNY\Drawings\WM-5\Wet Tapping_11152011 11:17 AM (img).tiff


11¼°, 22½°, 45°, AND 90° BENDS




DEAD END



TEE



TYPICAL CROSS SECTION



MINIMUM BEARING SURFACE AREA

SQUARE- FOOT AREA FOR
150 PSI INTERNAL PRESSURE PIPES

PIPE SIZE	BEND				TEE	DEAD END
	11 ¼°	22 ½°	45°	90°		
6"	0.6	1.3	2.5	4.6	2.3	3.1
8"	1.1	2.2	4.3	7.9	4.0	5.4
12"	2.4	4.6	9.1	16.8	8.6	11.4
16"	3.9	7.7	15.2	28.0	14.9	20.0
20"	8.5	17.0	33.5	61.7	32.7	43.6
24"	8.5	17.0	33.5	61.7	32.7	43.6
36"	18.9	37.5	73.5	135.0	72.0	96.0

REV. DATE

August 2012




MERIDIAN METROPOLITAN DISTRICT

CONCRETE THRUST BLOCK DETAILS


WM-6

MECHANICAL JOINT RESTRAINT FOR PVC - C-900 PIPE (TYPICAL)



PVC RESTRAINT - SERIES 2000 MEGALUG, SERIES 1500 UNI-FLANGE OR MMD
PRE-APPROVED EQUIVALENT; COLOR IS RED

MECHANICAL JOINT RESTRAINT FOR DUCTILE IRON PIPE (TYPICAL)



DUCTILE IRON RESTRAINT - SERIES 1100 MEGALUG, SERIES 1400 UNI-FLANGE OR
MMD PRE-APPROVED EQUIVALENT; COLOR IS BLACK

NOTE: DO NOT MODIFY RESTRAINTS AND INSTALL PER MANUFACTURES' RECOMMENDATION.

REV. DATE

August 2012








MERIDIAN METROPOLITAN DISTRICT

MECHANICAL JOINT RESTRAINT

WM-7

ROD DIAMETER, GRADE AND LENGTH OF RESTRAINED PIPE

PIPE SIZE	4"			6"			8"			12"			16"			20"			24"			30"		
	D	L	G	D	L	G	D	L	G	D	L	G	D	L	G	D	L	G	D	L	G	D	L	G
90° BEND, TEE, VALVE > 12", PLUG	$\frac{3}{4}$ "	40'	MS	$\frac{3}{4}$ "	45'	MS	$\frac{3}{4}$ "	60'	MS	$\frac{3}{4}$ "	86'	MS	$\frac{3}{4}$ "	108'	HS	1"	132'	HS	1"	155'	HS	1"	218'	HS
45° BEND	$\frac{3}{4}$ "	9'	MS	$\frac{3}{4}$ "	13'	MS	$\frac{3}{4}$ "	18'	MS	$\frac{3}{4}$ "	25'	MS	$\frac{3}{4}$ "	32'	MS	$\frac{3}{4}$ "	39'	HS	$\frac{3}{4}$ "	45'	HS	$\frac{3}{4}$ "	64'	HS
22 $\frac{1}{2}$ ° BEND	$\frac{3}{4}$ "	2'	MS	$\frac{3}{4}$ "	4'	MS	$\frac{3}{4}$ "	5'	MS	$\frac{3}{4}$ "	7'	MS	$\frac{3}{4}$ "	8'	MS	$\frac{3}{4}$ "	10'	MS	$\frac{3}{4}$ "	12'	MS	$\frac{3}{4}$ "	17'	MS
11 $\frac{1}{4}$ ° BEND	$\frac{3}{4}$ "	2'	MS	$\frac{3}{4}$ "	2'	MS	$\frac{3}{4}$ "	2'	MS	$\frac{3}{4}$ "	2'	MS	$\frac{3}{4}$ "	2'	MS	$\frac{3}{4}$ "	3'	MS	$\frac{3}{4}$ "	3'	MS	$\frac{3}{4}$ "	5'	MS
VERTICAL BENDS	ALL TOTALLY RESTRAINED, L = 40'																							



NOTES

1. LENGTH OF RESTRAINED PIPE MEASURED EACH WAY FROM VALVES AND BENDS.
2. CLAMPS, RODS & MEGALUGS NOT ALLOWED FOR PIPES LARGER THAN 30". CLAMPS AND RODS SHALL BE EXTENDED TO THE NEXT PIPE.
3. D=DIAMETER, L=LENGTH, G=GRADE, MS=MILD STEEL, HS=HIGH STRENGTH.
4. MIN 4.5' GROUND COVER REQUIRED.
5. BASED ON 150 PSI INTERNAL PRESSURE, FOR L AND PRESSURES LISTED ON SHEET 22 FOR D AND G.
6. MS = MILD STEEL ROD ASTM A-36. HS = HIGH STRENGTH ROD ASTM A-193 GRADE B7.
7. NUTS SHALL BE ASTM A-307 GRADE A OR B HEXAGON HEAVY SERIES.
8. SEE TIE ROD DETAIL DRAWING. ALSO, TIE ROD COUPLING DETAILS, CLAMP DETAILS AND SET CLAMP DETAILS.
9. LENGTH REFERS TO THE AMOUNT OF PIPE WHICH MUST BE RESTRAINED TOGETHER AND IS NOT NECESSARILY THE LENGTH OF THE RODS.
10. LENGTH OF RESTRAINED PIPE CHART IS ALSO FOR THE LENGTH OF JOINT RESTRAINT FOR MEGALUGS.
11. CROSSES MUST BE RESTRAINED IN ALL APPLICABLE DIRECTIONS.
12. 12" AND SMALLER IN LINE VALVES AND TEES SHALL HAVE A MECHANICAL JOINT RESTRAINT DEVICE ON EACH SIDE OF THE FITTING OR VALVE. MECHANICAL JOINT RESTRAINT DEVICE SHALL BE PER WM-11.
13. A SECOND VALVE WILL BE REQUIRED TO BE CLOSED WHEN EXCAVATING NEXT TO A EXISTING VALVE.
14. ON PLUGS, TEES AND BENDS KICKBLOCKS SHALL BE USED IN ADDITION TO RESTRAINT.
15. WHEN REDUCERS ARE USED ON VALVE INSTALLATIONS THE LENGTH OF RESTRAINT SHALL BE BASED ON THE SIZE OF THE PIPE NOT THE SIZE OF THE VALVE.

REV. DATE

August 2012




MERIDIAN METROPOLITAN DISTRICT

LENGTH OF RESTRAINED PIPE

WM-8

FLANGE LUG DETAIL

PIPE SIZE	N	O	H.S. RODS			M.S. RODS			R	S	U	V	PIPE SIZE
			P	Q	ROD Ø	P	Q	ROD Ø					
6"	1 $\frac{13}{16}$ "	2 $\frac{1}{4}$ "	1"	$\frac{7}{8}$ "	$\frac{3}{4}$ "	1"	$\frac{7}{8}$ "	$\frac{3}{4}$ "	$\frac{7}{8}$ "	$\frac{7}{8}$ "	3 $\frac{3}{4}$ "	$\frac{3}{4}$ "	6"
8"	2 $\frac{1}{4}$ "	2 $\frac{3}{4}$ "	1"	$\frac{7}{8}$ "	$\frac{3}{4}$ "	1"	$\frac{7}{8}$ "	$\frac{3}{4}$ "	1"	$\frac{7}{8}$ "	4 $\frac{7}{8}$ "	$\frac{3}{4}$ "	8"
12"	2 $\frac{3}{16}$ "	2 $\frac{3}{4}$ "	1 $\frac{1}{8}$ "	$\frac{7}{8}$ "	$\frac{3}{4}$ "	1 $\frac{1}{4}$ "	1 $\frac{1}{8}$ "	$\frac{3}{4}$ "	1 $\frac{1}{8}$ "	1"	7 $\frac{1}{4}$ "	$\frac{7}{8}$ "	12"
16"	2 $\frac{1}{16}$ "	2 $\frac{3}{4}$ "	1 $\frac{1}{8}$ "	$\frac{7}{8}$ "	$\frac{3}{4}$ "	1 $\frac{1}{2}$ "	1 $\frac{3}{8}$ "	$\frac{3}{4}$ "	1 $\frac{1}{4}$ "	1 $\frac{1}{8}$ "	9 $\frac{3}{8}$ "	1 $\frac{1}{8}$ "	16"
20"	1 $\frac{31}{32}$ "	2 $\frac{3}{4}$ "	1 $\frac{1}{4}$ "	1 $\frac{1}{8}$ "	1"	-	-	-	1 $\frac{7}{16}$ "	1 $\frac{1}{4}$ "	11 $\frac{1}{16}$ "	1 $\frac{1}{4}$ "	20"



REV. DATE

August 2012




MERIDIAN METROPOLITAN DISTRICT

FLANGE LUG DETAIL

WM-9

TIE-ROD RETAINING CLAMP

PIPE SIZE	ROD DIA.	A	B	C	D	E	F	G	H	I	J
4"	$\frac{3}{4}$ "	5"	$\frac{1}{2}$ " x $3\frac{1}{2}$ "	$\frac{1}{2}$ "	2"	$\frac{3}{4}$ "	0.660"	3.10"	1.13"	8.58"	16.28"
6"	$\frac{3}{4}$ "	$7\frac{1}{16}$ "	$\frac{1}{2}$ " x $3\frac{1}{2}$ "	$\frac{1}{2}$ "	2"	$\frac{3}{4}$ "	0.660"	3.10"	1.13"	10.64"	18.34"
8"	$\frac{3}{4}$ "	$9\frac{3}{16}$ "	$\frac{1}{2}$ " x $3\frac{1}{2}$ "	$\frac{1}{2}$ "	2"	$\frac{3}{4}$ "	0.660"	3.10"	1.13"	12.78"	20.48"
10"	$\frac{3}{4}$ "	$11\frac{3}{8}$ "	$\frac{1}{2}$ " x $3\frac{1}{2}$ "	$\frac{1}{2}$ "	2"	$\frac{3}{4}$ "	0.660"	3.10"	1.13"	14.96"	22.66"
12"	$\frac{3}{4}$ "	$13\frac{1}{2}$ "	$\frac{1}{2}$ " x $3\frac{1}{2}$ "	$\frac{1}{2}$ "	2"	$\frac{3}{4}$ "	0.660"	3.10"	1.13"	17.08"	24.78"
14"	1"	$15\frac{3}{4}$ "	$\frac{5}{8}$ " x $4\frac{1}{2}$ "	$\frac{3}{4}$ "	3"	$\frac{15}{16}$ "	0.780"	4.14"	1.69"	20.70"	30.86"
16"	1"	$17\frac{7}{8}$ "	$\frac{5}{8}$ " x $4\frac{1}{2}$ "	$\frac{3}{4}$ "	4"	$\frac{15}{16}$ "	0.780"	4.14"	1.69"	22.80"	32.96"
18"	1"	20"	$\frac{3}{4}$ " x 5"	$\frac{3}{4}$ "	4"	$1\frac{1}{8}$ "	0.950"	4.14"	1.69"	25.28"	35.81"
20"	1"	$22\frac{1}{8}$ "	$\frac{3}{4}$ " x 5"	$\frac{3}{4}$ "	4"	$1\frac{1}{8}$ "	0.950"	4.14"	1.69"	27.40"	37.93"
24"	$1\frac{1}{4}$ "	$26\frac{3}{8}$ "	$\frac{3}{4}$ " x $5\frac{1}{2}$ "	$\frac{3}{4}$ "	5"	$1\frac{1}{8}$ "	0.950"	5.18"	1.69"	31.66"	42.19"



NOTES:

1. DIMENSIONS ARE BASED ON BOX END WRENCH CLEARANCES.
2. DIMENSION "G" HAS BEEN SIZED TO ACCOMMODATED TWO (2) RODS, IF NEEDED.
3. STEEL PLATES OR WASHERS ARE TO BE USED TO SECURE TIE ROD.
4. CLAMPS SHALL BE EPOXY COATED.

REV. DATE


August 2012




MERIDIAN METROPOLITAN DISTRICT

TIE-ROD RETAINING CLAMP

WM-10



TYPICAL DETAIL FOR WATER LINE DEPRESSION
 4", 6" 8", 10" & 12" DIAMETERS



TYPICAL RESTRAINED JOINTS
 MAY USE MEG-A-LUG OR RODDING

REV. DATE

August 2012




MERIDIAN METROPOLITAN DISTRICT


RESTRAINED JOINTS AT VERTICAL BENDS

WM-11

IT\EGE\ENTER\proj\2008\06-24\wg\BLOC\SUB\Drawings\WM-11 Restrained Vertical Bending.dwg, 11/13/2012 11:49:50 AM, mmerquez, 1:1



ELEVATION




NOTES:


- 1 1/2" ROCK SHALL BE PLACED IN BOTTOM OF MANHOLE TO CROWN OF PIPE ONLY.
- ALL PIPE AND FITTINGS SHALL BE BRASS.
- 6" THRU 10" LINES SHALL HAVE, 2 EA., 1" COMBINATION AIR VALVE.
- 12" LINES AND LARGER SHALL HAVE, 2 EA., 2" COMBINATION AIR VALVE.
- SUPPORT BRACE SHALL BE CONSTRUCTED OF 1/4" STEEL STRAPPING DRILLED TO MATCH AIR PORT HOLES.

REV. DATE		MERIDIAN METROPOLITAN DISTRICT	WM-12
05/13			
AIR VALVE ASSEMBLY			


I:\TECHCENTER\projects\200606-24\wg\BAC\COCS\Utility\Drawings\WM-12_Air Valve Assembly.dwg, 5/10/2013 9:28:49 AM, linewd, 1:1




VENT SCREEN DETAIL



BASE DETAIL



ANGLE DETAIL



VENT SCREEN DETAIL

NOTE:
 1. COLOR SHALL BE DISTRICT GREY - SEE WM-3.


I:\TECHCENTER\projects\2008\06-24\img\BLOC\BUnit\Drawings\WM-13_Vent_Assembly_Detail.dwg, 11/13/2012 11:57:00 AM, (image).t11

REV. DATE
August 2012



MERIDIAN METROPOLITAN DISTRICT
AIR VENT DETAIL

WM-13




ELEVATION


NOTE:
 THIS INSTALLATION MAY BE REPLACED BY A FIRE HYDRANT WHERE PRE-APPROVED BY THE MERIDIAN METROPOLITAN DISTRICT.

REV. DATE		MERIDIAN METROPOLITAN DISTRICT		
05/13				
			TRANSMISSION MAIN BLOWOFF	
				WM-14

NOTE:
PLUG SHALL BE MECHANICALLY RESTRAINED (PER WM-8)



PLAN



ELEVATION

NOTE:
BLOWOFF PIPE TO BE TYPE K SOFT COPPER OR BRASS.

REV. DATE


August 2012



MERIDIAN METROPOLITAN DISTRICT

BLOWOFF FOR 12" AND SMALLER PIPE

WM-15



NOTE:

1. FITTINGS SHALL BE WRAPPED WITH 8 MIL THICKNESS POLYETHYLENE.

REV. DATE



05/13



MERIDIAN METROPOLITAN DISTRICT

VALVE BOX DETAIL

WM-16



NOTE:

1. PLATE SHALL BE COATED WITH LIQUID EPOXY, 16 MIL DRY FILM THICKNESS IN ACCORDANCE WITH AWWA C210.

REV. DATE


August 2012




MERIDIAN METROPOLITAN DISTRICT

VALVE BOX SUPPORT PLATE


WM-17



CENTERING WASHER



VALVE OPERATOR EXTENSION



VALVE EXTENSION GUIDE

NOTE:

1. BAR SHALL BE COATED WITH LIQUID EPOXY, 16 MIL DRY FILM THICKNESS IN ACCORDANCE WITH AWWA C210. BAR SHALL BE ASTM A 36.

REV. DATE


August 2012



MERIDIAN METROPOLITAN DISTRICT

VALVE OPERATOR GUIDE & EXTENTION

WM-18



REV. DATE



August 2012



MERIDIAN METROPOLITAN DISTRICT

ZONE VALVE MANHOLE

WM-19



NOTES:

1. EXTERIOR CONCRETE SHALL BE DAMP-PROOFED IN ACCORDANCE WITH THE SPECIFICATIONS.
2. CONNECT GALVANIZED SCREEN TO VENT PIPE WITH HOSE CLAMP AROUND PIPE - TYPICAL.
3. ALL FITTINGS AND PIPING WILL BE PAINTED "PRECAUTION BLUE" ENAMEL.
4. IF PRV IS LOCATED IN A PAVED AREA, THE ACCESS WILL BE A 36" DIA. RING & COVER. VAULT LID SHALL HAVE A REMOVABLE SECTION (MIN. 6' WIDE) WITH LIFTING RING. VENTS TO BE LOCATED IN THE NEAREST LANDSCAPE AREA WITH DISTRICT APPROVAL.
5. SEE WM-20A FOR ADDITIONAL DETAILS.

REV. DATE

06/12



MERIDIAN METROPOLITAN DISTRICT

PRESSURE REDUCING VAULT


WM-20


LABEL DESCRIPTIONS FOR WM-20:

- ① 4" DIP CLASS 50.
- ② "d" GATE VALVE (MATCH THE SIZE OF THE MAIN).
- ③ "d" PRESSURE REDUCING/SUSTAINING VALVE (CLA-VAL SERIES 92G-01); GPM TO 3900.
- ④ 4" PRESSURE REDUCING/SUSTAING VALVE (CLA-VAL SERIES 92G-01); GPM TO 580.
- ⑤ DRESSER STYLE PIPE COUPLING.
- ⑥ 4" GATE VALVE.
- ⑦ SUMP AND COVER.
- ⑧ 3/4" CORP. WITH IRON PIPE THREAD OUTLET & PRESSURE GAUGE WITH 4" FACE & 5 PSI INCREMENTS (0-200 PSI RANGE) - TYPICAL.
- ⑨ PIPE SUPPORTS - SEE D-4 AND D-5.
- ⑩ RECTANGULAR PRECAST VAULT, TOP, BOTTOM & SIDES.
- ⑪ MEGA LUG PIPE RESTRAINTS.
- ⑫ 4" DRESSER STYLE COUPLING.
- ⑬ "d" x 8" TEE.

NOTES FOR WM-20

- 1. "d" = DIAMETER OF MAIN LINE PIPE.
- 2. ALL BACKFILL SHALL BE COMPACTED TO 90% ASTM 1557.
- 3. ACTUAL LENGTHS OF PIPE TO BE FIELD VERIFIED BY CONTRACTOR.
- 4. PIPE NOT SHOWN IN TRUE GEOGRAPHICAL POSITION FOR CLARITY.


REV. DATE 06/12		MERIDIAN METROPOLITAN DISTRICT PRESSURE REDUCING VAULT NOTES	WM-20A
--------------------	---	--	--------



NOTES:

1. FOR LOTS WITH JOINT TRENCH ALONG FRONT OF LOT, WATER SERVICE LINE SHALL BE PLACED WITH 4.5' MINIMUM COVER.
2. ALL WATER SERVICES SHALL BE PLACED AT THE CENTER OF THE LOT.
3. A "V" SHALL BE CUT IN THE FACE OF THE CURB AND GUTTER BY THE BUILDER TO PERMANENTLY MARK THE LOCATION OF THE CURB STOP BOX.
4. THIS DETAIL IS FOR CENTER OF FRONT LOT ONLY.

REV. DATE		MERIDIAN METROPOLITAN DISTRICT	WS-1
06/12		WATER AND SEWER JOINT TRENCH	



NOTES:

1. WATER SERVICE LINES SHALL ONLY BE PERMITTED IN THE FRONT OF LOTS. CURB STOP VALVE LOCATIONS SHALL COMPLY WITH DETAIL WS-5, WS-6 AND WS-7.
2. A 3 INCH "V" SHALL BE CUT IN THE FACE OF THE CURB AND GUTTER BY THE BUILDER TO PERMANENTLY MARK THE LOCATION OF THE CURB STOP BOX.
3. WATER MAIN SERVICE CONNECTION SHALL FOLLOW DETAIL WS-3

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

RESIDENTIAL WATER SERVICE LOCATION

WS-2



- ① WATER MAIN WITH TAPPING SADDLE
- ② INLET SIDE - AWWA TAPER THREAD (CC STYLE)
- ③ CORPORATION STOP, FORD #FB1000, MUELLER #H15008 & #H15013, MCDONALD & 4701BQ & 4701BT OR APPROVED EQUAL
- ④ TYPE K COPPER PIPE
- ⑤ PROVIDE AMPLE BEND
- ⑥ OUTLET SIDE - GRIP TITE JOINT COMPRESSION
- ⑦ TYLER 6500 SERIES, 95E, 4 $\frac{7}{8}$ " DROP LID VARIABLE EXTENSION SHAFT WITH 5'0" TO 7'0" RANGE
- ⑧ CURB STOP WITH GRIP TITE COMPRESSION OUTLETS (FORD B44G, MUELLER B25209 MCDONALD #6100-Q OR APPROVED EQUAL) 2" SQUARE NUT FOR 1.5" AND 2" BALL VALVES
- ⑨ TYPE K COPPER PIPE
- ⑩ 12" x 12" x 2" CONCRETE PAD PLACED UNDER CURB STOP VALVE & BOX

NOTES:

1. PLACE STOP BOX WITHIN 5 FT OF PROPERTY LINE. PLACEMENT INSIDE PROPERTY LINE IS PREFERRED.
2. PROPERTY OWNER IS RESPONSIBLE FOR THE ENTIRE SERVICE LINE (REPLACEMENT & REPAIRS) AND LEAKS FROM THE CURB STOP TO THE METER. MMD WILL REPAIR SERVICE LINE LEAKS BETWEEN THE WATER MAIN AND THE OUTLET SIDE OF THE CURB STOP ONLY (SEE WS-7).
3. NO BENDS, FITTINGS, CONNECTIONS, OR CHANGES IN THE PIPE SIZE ARE PERMITTED ON THE SERVICE LINE FROM THE CORPORATION STOP TO THE METER OUTLET VALVES EXCEPT AS SHOWN.
4. MMD IS NOT RESPONSIBLE FOR ANY DAMAGE THAT MAY OCCUR DUE TO A LEAK ANYWHERE ON THE SERVICE LINE. ALL DAMAGE IS THE RESPONSIBILITY OF THE PROPERTY OWNER.
5. A 3 INCH "V" SHALL BE CUT IN THE FACE OF THE CURB AND GUTTER TO PERMANENTLY MARK THE LOCATION OF THE CURB STOP BOX.

REV. DATE


05/13



MERIDIAN METROPOLITAN DISTRICT

WATER MAIN SERVICE CONNECTION

WS-3



NOTES:

1. CURB STOP BOX SHALL BE TYLER MODEL 6500 SERIES, SIZE 95E OR APPROVED EQUAL
2. ALL SECTIONS OF THE BOX SHALL BE WRAPPED IN 8 MIL POLYETHYLENE PLASTIC.
3. A 12" x 12" x 2" CONCRETE PAD SHALL BE PLACED UNDER THE CURB STOP VALVE AND BOX.

REV. DATE


05/13



MERIDIAN METROPOLITAN DISTRICT

CURB STOP FOR $\frac{3}{4}$ " AND 1" LINES

WS-4



NOTES:

1. A "V" SHALL BE CUT IN THE FACE OF THE CURB AND GUTTER BY THE BUILDER TO PERMANENTLY MARK THE LOCATION OF THE CURB STOP BOX. THE "V" SHALL BE A MINIMUM OF 3 INCHES IN HEIGHT AND $\frac{1}{8}$ " DEEP.
2. ALL WATER SERVICE LINES SHALL BE PLACED AT THE CENTER OF THE LOT.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

CURB STOP BOX LOCATION

WS-5



NOTES:

1. A "V" SHALL BE CUT IN THE FACE OF THE CURB AND GUTTER BY THE BUILDER TO PERMANENTLY MARK THE LOCATION OF THE CURB STOP BOX. THE "V" SHALL BE A MINIMUM OF 3 INCHES IN HEIGHT AND 1/8" DEEP.
2. ALL WATER SERVICE LINES SHALL BE PLACED AT THE CENTER OF THE LOT.
3. DISTANCE BETWEEN BACK OF CURB AND WALK MAY INCREASE DEPENDING ON ROW WIDTH.

REV. DATE
06/12




MERIDIAN METROPOLITAN DISTRICT

CURB STOP BOX LOCATION FOR DETACHED WALK

WS-6

I:\TECHCENTER\projects\2008\06-24\Map\BLOCK\Utility\Drawings\WS-6-Curb Stop Location Detached Walk.dwg, 11/13/2012 12:17:52 PM, mringaz, 1'



NOTES:

1. A "V" SHALL BE CUT IN THE FACE OF THE CURB AND GUTTER BY THE BUILDER TO PERMANENTLY MARK THE LOCATION OF THE CURB STOP BOX. THE "V" SHALL BE A MINIMUM OF 3 INCHES IN HEIGHT AND $\frac{1}{8}$ " DEEP.
2. ALL WATER SERVICE LINES SHALL BE PLACED AT THE CENTER OF THE LOT.
3. DISTANCE BETWEEN BACK OF CURB AND WALK MAY INCREASE DEPENDING ON ROW WIDTH.
4. SEE WS-8, WS-9 AND WS-10 FOR CURB STOP LOCATION FOR COMMERCIAL TAP AND SERVICE LINE DETAIL. SEE WS-5 AND WS-6 FOR THE CURB STOP LOCATION FOR A RESIDENTIAL SERVICE.
5. SHOULD ANY SITUATION ARISE OTHER THAN SHOWN CONCERNING THE DEPTH OR OBSTRUCTION OF SERVICE LINE THE DISTRICT MUST BE CONTACTED.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT


STANDARD WATER SERVICE LINE INSTALLATION

WS-7



- ① EXISTING MAIN
- ② TAPPING SLEEVE
- ③ TAPPING VALVE W/ RISER
- ④ SERVICE/FIRELINE
- ⑤ CONC. KICKBLOCK (WM-6)
- ⑥ M.J. ANCHORING TEE (SWIVEL TEE)
- ⑦ POLYETHYLENE WRAPPED

TAPPING DETAIL



NOTES:

1. A "V" SHALL BE CUT IN THE FACE OF THE CURB AND GUTTER BY THE BUILDER TO PERMANENTLY MARK THE LOCATION OF THE CURB STOP BOX. THE "V" SHALL BE A MINIMUM OF 3 INCHES IN HEIGHT AND 1/8" DEEP.
2. SEE WS-8, WS-9 AND WS-10 FOR CURB STOP LOCATION FOR COMMERCIAL TAP AND SERVICE LINE DETAIL. SEE WS-10 FOR FIRE MAIN AND DOMESTIC WATER SERVICE INSTALLATION.
3. THE TAP REQUIREMENTS FOR THE IRRIGATION CONNECTION ARE THE SAME AS THE FIRE MAIN AND DOMESTIC WATER SERVICE INSTALLATION.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT


SERVICE CONNECTION TO EXISTING STUB UNDER STREET

WS-8



- ① EXISTING MAIN
- ② TAPPING SLEEVE
- ③ TAPPING VALVE W/ RISER
- ④ SERVICE/FIRELINE
- ⑤ CONC. KICKBLOCK (WM-6)
- ⑥ M.J. ANCHORING TEE (SWIVEL TEE)
- ⑦ POLYETHYLENE WRAPPED

TAPPING DETAIL



NOTES:

1. A "V" SHALL BE CUT IN THE FACE OF THE CURB AND GUTTER BY THE BUILDER TO PERMANENTLY MARK THE LOCATION OF THE CURB STOP BOX. THE "V" SHALL BE A MINIMUM OF 3 INCHES IN HEIGHT AND 1/8" DEEP.
2. SEE WS-8, WS-9 AND WS-10 FOR CURB STOP LOCATION FOR COMMERCIAL TAP AND SERVICE LINE DETAIL. SEE WS-10 FOR FIRE MAIN AND DOMESTIC WATER SERVICE INSTALLATION.
3. THE TAP REQUIREMENTS FOR THE IRRIGATION CONNECTION ARE THE SAME AS THE FIRE MAIN AND DOMESTIC WATER SERVICE INSTALLATION.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

SERVICE/FIRE OR IRRIGATION CONNECTION TO MAIN

WS-9



NOTES:

1. ALL DOMESTIC TAPS 2" AND SMALLER ON FIRE LINES 6" D.I.P. AND LARGER REQUIRE A DOUBLE STRAP BRONZE TAPPING SADDLE.
2. ON 4" FIRE MAINS FOR 2" TAP USE 4" M.J. X 2" THREADED TEE.
3. FOR 1½" TAP USE 4" M.J. X 2" THREADED TEE WITH 1 ½" BRASS BUSHING.
4. FOR ¾" AND 1" SERVICE LINES REQUIRE A DOUBLE STRAP BRONZE TAPPING SADDLE.
5. RESTRAIN MAIN AND FIRE MAIN PER WM-8.
6. A PRESSURE REDUCING VALVE IS REQUIRED BEFORE THE METER IF STATIC PRESSURE IS GREATER THAN 95 PSI.

REV. DATE




06/12



MERIDIAN METROPOLITAN DISTRICT

FIRE MAIN AND DOMESTIC WATER SERVICE INSTALLATION

WS-10



NOTES:

1. THE METER SHALL BE PROTECTED FROM FREEZING AND DAMAGE.
2. THE METER SHALL BE ANCHORED TO THE WALL ABOVE AND BELOW THE METER ASSEMBLY.
3. ALL METER LOCATIONS TO BE IN BASEMENTS AND NOT IN CRAWL SPACES.
4. WATER SERVICE LINE SHALL BE TYPE K COPPER.
5. NO BENDS, FITTINGS, CONNECTIONS, OR CHANGES IN THE PIPE SIZE ARE PERMITTED ON THE SERVICE LINE FROM THE CORPORATION STOP TO THE METER OUTLET VALVE EXCEPT AS SHOWN.
6. IF THE METER IS BOXED IN OR PLACED BEHIND A WALL, PROVIDE AN ACCESS OPENING 36" WIDE FROM ABOVE THE OUTLET VALVE TO THE FLOOR. VALVES MUST BE ACCESSIBLE FROM THE OPENING. METER TO BE CENTERED IN OPENING.
7. A PRESSURE REDUCING VALVE IS REQUIRED BEFORE THE METER IF STATIC PRESSURE IS GREATER THAN 95 PSI.

REV. DATE




11/13



MERIDIAN METROPOLITAN DISTRICT

REMOTE READING $\frac{3}{4}$ " & 1" METER TYPICAL INSIDE SETTING

WS-11



NOTES:

1. THE METER SHALL BE PROTECTED FROM FREEZING AND DAMAGE.
2. THE METER SHALL BE ANCHORED TO THE WALL ABOVE AND BELOW THE METER ASSEMBLY.
3. ALL METER LOCATIONS TO BE IN BASEMENTS AND NOT IN CRAWL SPACES.
4. WATER SERVICE LINE SHALL BE TYPE K COPPER.
5. NO BENDS, FITTINGS, CONNECTIONS, OR CHANGES IN THE PIPE SIZE ARE PERMITTED ON THE SERVICE LINE FROM THE CORPORATION STOP TO THE METER OUTLET VALVE EXCEPT AS SHOWN.
6. IF THE METER IS BOXED IN OR PLACED BEHIND A WALL, PROVIDE AN ACCESS OPENING 36" WIDE FROM ABOVE THE OUTLET VALVE TO THE FLOOR. VALVES MUST BE ACCESSIBLE FROM THE OPENING. METER TO BE CENTERED IN OPENING.
7. A PRESSURE REDUCING VALVE IS REQUIRED BEFORE THE METER IF STATIC PRESSURE IS GREATER THAN 95 PSI.

REV. DATE


11/13



MERIDIAN METROPOLITAN DISTRICT

REMOTE READING $\frac{3}{4}$ " & 1" METER TYPICAL INSIDE SETTING
(COMMERCIAL)

WS-11A



NOTES:

1. ALL METER PITS LOCATED IN CONCRETE, WHEN PERMITTED, SHALL HAVE A CAST IRON DOME & COVER.
2. METER SETTER SHALL BE FORD 70 SERIES TANDEM COPPER SETTER, MODEL TV 73-36W. FOR $\frac{3}{4}$ " SERVICE WITH PADLOCK WINGS ON INLET VALVE & COMPRESSION END CONNECTIONS.
3. ALL METER PITS SHALL HAVE A 2" HOLE IN THE CENTER OF THE LID FOR THE PURPOSE OF INSTALLING A REMOTE SENSING UNIT.
4. THERE SHALL NOT BE LESS THAN 4.5' OF COVER OVER THE PIPE.
5. METER SETTER FOR 1" SERVICE SHALL BE FOR 70 SERIES TANDEM COPPER SETTER, MODEL TV 74-36W, WITH PADLOCK WINGS ON INLET VALVE & COMPRESSION END CONNECTIONS.
6. WHEN USED FOR AN IRRIGATION SYSTEM, AN APPROVED BACK FLOW PROTECTION DEVICE MUST BE INCLUDED, ALONG WITH A STOP AND WASTE VALVE ON THE CUSTOMERS SIDE OF THE PIT.
7. FOR $\frac{3}{4}$ " METER SIZE $L=7\frac{1}{2}$ "; FOR 1" METER SIZE $L=10\frac{3}{4}$ ".
8. A PRESSURE REDUCING VALVE IS REQUIRED BEFORE THE METER IF STATIC PRESSURE IS GREATER THAN 95 PSI.

REV. DATE



06/12



MERIDIAN METROPOLITAN DISTRICT

METER PIT FOR $\frac{3}{4}$ " & 1" METER TANDEM SETTER

WS-11B



- ① 90° ELBOW
- ② TEE
- ③ LOCKABLE VALVE
- ④ METER UNIT
- ⑤ CHECK VALVE
- ⑥ TYPE K COPPER
- ⑦ WIRE SHIELDED CABLE TO TOUCH READ REGISTER
- ⑧ TOUCH READ METER
- ⑨ INSIDE MXLL RADIO READ UNIT

NOTES:

1. THE METER SHALL BE PROTECTED FROM FREEZING AND DAMAGE.
2. WATER SERVICE LINE SHALL BE TYPE K COPPER.
3. NO BENDS, FITTINGS, CONNECTIONS, OR CHANGES IN THE PIPE SIZE ARE PERMITTED ON THE SERVICE LINE FROM THE CORPORATION STOP TO THE METER OUTLET VALVE EXCEPT AS SHOWN.
4. PIPE JOINTS SHALL BE THREADED, FLANGED OR SOLDERED W/95-5 TIN-ANTIMONY SOLDER.
5. COMPANION FLANGES SHALL BE BRASS.
6. A FLOOR DRAIN SHALL BE PLACED NEAR THE METER INSTALLATION.
7. A PRESSURE REDUCING VALVE IS REQUIRED BEFORE THE METER IF STATIC PRESSURE IS GREATER THAN 95 PSI.

REV. DATE
06/12





MERIDIAN METROPOLITAN DISTRICT

INSIDE SETTING FOR 1 1/2" AND LARGER WATER METER WITH BYPASS

WS-12

W:\ENGINEER\projects\2008\06-24\MD\BLOCCK\Utility\Drawings\12 Inside Setting for 1.5 in and larger water meter and by pass.dwg, 11/13/2012, 12:26:54 PM, msaquet, 1:1





- ① GATE VALVE
- ② SCREW GATE VALVE
- ③ 1¼" BALL VALVE WITH LOCKING WING
- ④ FORD CUSTOM SETTER TEE
- ⑤ COMP. COPPER X MIPT ADAPTER
- ⑥ CLOSE BRASS NIPPLE
- ⑦ 1¼" X CLOSE BRASS NIPPLE
- ⑧ 90° BEND
- ⑨ MIPT X SWEAT ADAPTER
- ⑩ BRASS METER FLANGE
- ⑪ LOC-PAC COUPLING
- ⑫ CUT TYPE K - COPPER PIPE
- ⑬ PRESSURE REDUCING VALVE

NOTES:

1. THE METER SHALL BE PROTECTED FROM FREEZING AND DAMAGE.
2. WATER SERVICE LINE SHALL BE TYPE K COPPER.
3. NO BENDS, FITTINGS, CONNECTIONS, OR CHANGES IN THE PIPE SIZE ARE PERMITTED ON THE SERVICE LINE FROM THE CORPORATION STOP TO THE METER OUTLET VALVE EXCEPT AS SHOWN.
4. PIPE JOINTS SHALL BE THREADED, FLANGED OR SOLDERED W/95-5 TIN-ANTIMONY SOLDER.
5. METER YOKE LENGTH (L): 13" FOR 1 ½" METER; 17" FOR 2" METER.
6. THE ASSEMBLY SHALL BE INSTALLED AT AN ELEVATION OF 48" ABOVE THE FINISHED FLOOR. THE ASSEMBLY SHALL BE PLACED 12" AWAY FROM THE ADJACENT WALL TO THE CENTER OF THE ASSEMBLY WITH A MINIMUM OF 24" CLEAR SPACE IN FRONT OF THE ASSEMBLY FROM FLOOR TO CEILING. IF THE WATER METER AND BACKFLOW PREVENTION ASSEMBLY ARE TO BE INSTALLED IN SERIES, THERE SHALL BE A MINIMUM OF 24" CLEARANCE BETWEEN THE ASSEMBLIES.
7. A PRESSURE REDUCING VALVE IS REQUIRED BEFORE THE METER IF STATIC PRESSURE IS GREATER THAN 95 PSI.

I:\TECHCENTER\projects\2008\06-24\Map\BLOCK\BUD\DWG\WS-13 Typical Water Meter for 1.5 and 2 inch.dwg, 11/13/2012 12:26:17 PM, rmezzac, 11

REV. DATE 06/12		MERIDIAN METROPOLITAN DISTRICT TYPICAL WATER METER ASSEMBLY FOR 1 ½" AND 2" METERS	WS-13
--------------------	---	--	--------------




- ① GATE VALVE
- ② SCREW GATE VALVE
- ③ 1¼" BALL VALVE WITH LOCKING WING
- ④ FORD CUSTOM SETTER TEE
- ⑤ COMP. COPPER X MIPT ADAPTER
- ⑥ CLOSE BRASS NIPPLE
- ⑦ 1¼" X CLOSE BRASS NIPPLE
- ⑧ 90° BEND
- ⑨ MIPT X SWEAT ADAPTER
- ⑩ BRASS METER FLANGE
- ⑪ LOC-PAC COUPLING
- ⑫ CUT TYPE K - COPPER PIPE
- ⑬ PRESSURE REDUCING VALVE
- ⑭ REDUCED PRESSURE PRINCIPAL ASSEMBLY BACKFLOW PREVENTOR

NOTES:

1. THE METER SHALL BE PROTECTED FROM FREEZING AND DAMAGE.
2. WATER SERVICE LINE SHALL BE TYPE K COPPER.
3. NO BENDS, FITTINGS, CONNECTIONS, OR CHANGES IN THE PIPE SIZE ARE PERMITTED ON THE SERVICE LINE FROM THE CORPORATION STOP TO THE METER OUTLET VALVE EXCEPT AS SHOWN.
4. PIPE JOINTS SHALL BE THREADED, FLANGED OR SOLDERED W/95-5 TIN-ANTIMONY SOLDER.
5. METER YOKE LENGTH (L): 13" FOR 1 ½" METER; 17" FOR 2" METER.
6. THE ASSEMBLY SHALL BE INSTALLED AT AN ELEVATION OF 48" ABOVE THE FINISHED FLOOR. THE ASSEMBLY SHALL BE PLACED 12" AWAY FROM THE ADJACENT WALL TO THE CENTER OF THE ASSEMBLY WITH A MINIMUM OF 24" CLEAR SPACE IN FRONT OF THE ASSEMBLY FROM FLOOR TO CEILING. IF THE WATER METER AND BACKFLOW PREVENTION ASSEMBLY ARE TO BE INSTALLED IN SERIES, THERE SHALL BE A MINIMUM OF 24" CLEARANCE BETWEEN THE ASSEMBLIES.
7. A PRESSURE REDUCING VALVE IS REQUIRED BEFORE THE METER IF STATIC PRESSURE IS GREATER THAN 95 PSI.

I:\TECHCENTER\projects\2008\06-24\MC\BLOC\BUNNY\Drawings\14 Typical Water Meter and Backflow Preventor Assembly.dwg, 11/13/2010, 12:23:31 PM, imquanz, 1:1

REV. DATE		MERIDIAN METROPOLITAN DISTRICT TYPICAL WATER METER AND BACKFLOW PREVENTOR ASSEMBLY	WS-14	
06/12				



- | | |
|--------------------|--|
| ① GATE VALVE | ⑤ BYPASS (MIN. OF 2" DIAMETER LINE) |
| ② TEE | ⑥ REDUCED PRESSURE PRINCIPAL BACKFLOW PREVENTOR ASSEMBLY |
| ③ DRESSER COUPLING | ⑦ LOCKABLE VALVE |
| ④ METER | ⑧ FLANGED PRESSURE REDUCING VALVE |

NOTES:

1. THE METER SHALL BE PROTECTED FROM FREEZING AND DAMAGE.
2. WATER SERVICE LINE SHALL BE TYPE K COPPER.
3. NO BENDS, FITTINGS, CONNECTIONS, OR CHANGES IN THE PIPE SIZE ARE PERMITTED ON THE SERVICE LINE FROM THE CORPORATION STOP TO THE METER OUTLET VALVE EXCEPT AS SHOWN.
4. PIPE JOINTS SHALL BE THREADED, FLANGED OR SOLDERED W/95-5 TIN-ANTIMONY SOLDER.
5. THE ASSEMBLY SHALL BE INSTALLED AT AN ELEVATION OF 48" ABOVE THE FINISHED FLOOR. THE ASSEMBLY SHALL BE PLACED 12" AWAY FROM THE ADJACENT WALL TO THE CENTER OF THE ASSEMBLY WITH A MINIMUM OF 24" CLEAR SPACE IN FRONT OF THE ASSEMBLY FROM FLOOR TO CEILING. IF THE WATER METER AND BACKFLOW PREVENTION ASSEMBLY ARE TO BE INSTALLED IN SERIES, THERE SHALL BE A MINIMUM OF 24" CLEARANCE BETWEEN THE ASSEMBLIES.
6. A PRESSURE REDUCING VALVE IS REQUIRED BEFORE THE METER IF STATIC PRESSURE IS GREATER THAN 95 PSI.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

DOMESTIC STANDARD 3" & 4" METER AND BACKFLOW
ASSEMBLY DRAWING

WS-15



- ① GATE VALVE
- ② TEE
- ③ DRESSER COUPLING
- ④ METER
- ⑤ BYPASS (MIN. OF 2" DIAMETER LINE)
- ⑥ REDUCED PRESSURE PRINCIPAL BACKFLOW PREVENTOR ASSEMBLY
- ⑦ LOCKABLE VALVE
- ⑧ FLANGED PRESSURE REDUCING VALVE

NOTES:

1. THE METER SHALL BE PROTECTED FROM FREEZING AND DAMAGE.
2. WATER SERVICE LINE SHALL BE TYPE K COPPER.
3. NO BENDS, FITTINGS, CONNECTIONS, OR CHANGES IN THE PIPE SIZE ARE PERMITTED ON THE SERVICE LINE FROM THE CORPORATION STOP TO THE METER OUTLET VALVE EXCEPT AS SHOWN.
4. PIPE JOINTS SHALL BE THREADED, FLANGED OR SOLDERED W/95-5 TIN-ANTIMONY SOLDER.
5. THE ASSEMBLY SHALL BE INSTALLED AT AN ELEVATION OF 48" ABOVE THE FINISHED FLOOR. THE ASSEMBLY SHALL BE PLACED 12" AWAY FROM THE ADJACENT WALL TO THE CENTER OF THE ASSEMBLY WITH A MINIMUM OF 24" CLEAR SPACE IN FRONT OF THE ASSEMBLY FROM FLOOR TO CEILING. IF THE WATER METER AND BACKFLOW PREVENTION ASSEMBLY ARE TO BE INSTALLED IN SERIES, THERE SHALL BE A MINIMUM OF 24" CLEARANCE BETWEEN THE ASSEMBLIES.
6. A PRESSURE REDUCING VALVE IS REQUIRED BEFORE THE METER IF STATIC PRESSURE IS GREATER THAN 95 PSI.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT


DOMESTIC STANDARD 3" & 4" METER AND BACKFLOW
ASSEMBLY DRAWING

WS-16



NOTES:

1. "L" = DISTANCE FROM THE WALL TO THE CENTER OF THE ASSEMBLY.
2. ASSEMBLY SIZES: FOR $\frac{1}{4}$ " THRU $\frac{3}{4}$ ", L=3 INCHES; FOR 1" THRU 2", L=6 INCHES; AND 2 $\frac{1}{2}$ " AND LARGER, L=12 INCHES.
3. THE OFFSET FROM THE WALL TO THE CENTER OF THE ASSEMBLY ONLY APPLIES WHEN THE TEST COCKS ARE POINTED UP OR AWAY FROM THE ADJACENT WALL. OTHERWISE THE ASSEMBLY SHALL BE PLACED 12 INCHES AWAY FROM THE ADJACENT WALL.



NOTES:

1. THE BACKFLOW PREVENTER IS REQUIRED TO BE DOWNSTREAM OF THE WATER METER ASSEMBLY.
2. THE DRAIN FROM THE BACKFLOW PREVENTER SHALL NOT EXTEND OUTSIDE THE STRUCTURE TO DAYLIGHT.

REV. DATE



06/12



MERIDIAN METROPOLITAN DISTRICT

TYPICAL LOCATION FOR REDUCED PRESSURE
PRINCIPAL BACKFLOW PREVENTERS ASSEMBLY

WS-17



NOTES:

1. THE BACKFLOW PREVENTER IS REQUIRED TO BE DOWNSTREAM OF THE WATER METER ASSEMBLY.
2. THE DRAIN FROM THE BACKFLOW PREVENTER SHALL NOT EXTEND OUTSIDE THE STRUCTURE TO DAYLIGHT.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

TYPICAL LOCATION FOR REDUCED PRESSURE PRINCIPAL
BACKFLOW PREVENTER ASSEMBLY (2 1/2" & LARGER)

WS-18



NOTES:

1. THE BACKFLOW PREVENTER IS REQUIRED TO BE DOWNSTREAM OF THE WATER METER ASSEMBLY.
2. THE DRAIN FROM THE BACKFLOW PREVENTER SHALL NOT EXTEND OUTSIDE THE STRUCTURE TO DAYLIGHT.

REV. DATE


06/12




MERIDIAN METROPOLITAN DISTRICT

TYPICAL INSTALLATION FOR REDUCED PRESSURE
PRINCIPAL BACKFLOW PREVENTORS ASSEMBLY IN SERIES

WS-19



FRONT VIEW



SIDE VIEW

NOTES:

1. THE BACKFLOW PREVENTER IS REQUIRED TO BE DOWNSTREAM OF THE WATER METER ASSEMBLY.
2. THE DRAIN FROM THE BACKFLOW PREVENTER SHALL NOT EXTEND OUTSIDE THE STRUCTURE TO DAYLIGHT.

REV. DATE



06/12



MERIDIAN METROPOLITAN DISTRICT

TYPICAL VERTICAL BACKFLOW PREVENTER INSTALLATION



WS-20



- NOTES:**
1. BACKFLOW PREVENTER MAY BE REQUIRED UPON RECOMMENDATION OF DISTRICT.
 2. THE DISTANCE BETWEEN THE PRV AND METER SHALL BE AT LEAST 3 PIPE DIAMETERS SEPARATION.
 3. WHEN METER VAULT AND/OR CURB STOP BOX IS LOCATED IN LANDSCAPED AREAS A 6" CONCRETE COLLAR IS REQUIRED AROUND THE MANHOLE AND STOP BOX.
 4. A PRESSURE REDUCING VALVE IS REQUIRED BEFORE THE METER IF STATIC PRESSURE IS GREATER THAN 95 PSI.

REV. DATE		MERIDIAN METROPOLITAN DISTRICT	WS-21
06/12			
		STANDARD SETTING FOR 1 1/2" & 2" DOMESTIC METER VAULT	

I:\TECHCENTER\projects\2008\06-24\MD\BCC\BUD\10\Drawings\WS-21 Setting for 1.5 and 2 inch domestic meter vault.dwg, 11/13/2012, 12:38:04 PM, mmanquez, 1:1



NOTES:

1. BACKFLOW PREVENTER MAY BE REQUIRED UPON RECOMMENDATION OF DISTRICT.
2. A MINIMUM OF 6" OF $\frac{3}{4}$ " CRUSHED ROCK SHALL BE PLACED UNDER THE ENTIRE VAULT (SEE WS-23).
3. WHEN METER VAULT AND/OR CURB STOP BOX IS LOCATED IN LANDSCAPED AREAS A 6" CONCRETE COLLAR IS REQUIRED AROUND THE MANHOLE AND THE GATE VALVE.
4. A PRESSURE REDUCING VALVE IS REQUIRED BEFORE THE METER IF STATIC PRESSURE IS GREATER THAN 95 PSI.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

STANDARD SETTING FOR 3" & 4" DOMESTIC METER VAULT


WS-22



NOTES:

1. A MINIMUM OF 6" OF $\frac{3}{4}$ " CRUSHED ROCK SHALL BE PLACED UNDER THE ENTIRE VAULT.
2. WHEN METER VAULT AND/OR CURB STOP BOX IS LOCATED IN LANDSCAPED AREAS A 6" CONCRETE COLLAR IS REQUIRED AROUND THE MANHOLE AND THE GATE VALVE (SEE WS-22 FOR ADDITIONAL DETAILS).
3. RAMNEK ALL EXTERIOR JOINTS.

REV. DATE		MERIDIAN METROPOLITAN DISTRICT	WS-23
06/12			
		STANDARD FOR 3" & 4" DOMESTIC METER VAULT	



12" MINIMUM ABOVE
HIGHEST SPRINKLER HEAD

PRESSURE TYPE VACUUM
BREAKER WITH ISOLATION
GATE VALVES & TEST COCKS

SPRINKLER
HEADS (TYP.)

SOLENOID VALVE OR
GATE VALVE (TYP.)

PIPING SHALL BE "K" COPPER
BETWEEN SHUTOFF VALVE AND
VACUUM BREAKER

GATE
VALVE

FLOW

FLOW

WATER
METER

STOP & WASTE GATE VALVE
OR STOP & WASTE BALL VALVE

BASEMENT WALL

PRESSURE
REDUCING
VALVE

GATE VALVE
WITH DRAIN

NOTES:

1. RESIDENTIAL METER SETTING PER WS-11.

REV. DATE

06/12




MERIDIAN METROPOLITAN DISTRICT

RESIDENTIAL IRRIGATION SYSTEM
PRESSURE VACUUM BREAKER

WS-24

I:\TECHCENTER\projects\2008\06-24\MSJ\BLOCCK\DWG\Drawings\WS-24 Residential Irrigation System - Pressure Vacuum Breaker.dwg, 11/03/2012 12:36:19 PM, mjangaz, 1:1

- ① TOUCH READ METER
- ② TOUCH READ PAD
- ③ SHIELDED CABLE 3-WIRE
- ④ STOP & WASTE VALVE WITH 2" BY 9" CONCRETE PAD



OWNER'S RESPONSIBILITY

COVER FOR METER PIT & CURB STOP SHALL BE INSTALLED AND MAINTAINED LEVEL WITH THE ADJACENT GROUND

NOTES:

1. OWNER'S RESPONSIBILITY SHALL BE UP TO THE IRRIGATION SLEEVE OR TEE OR STUB.
2. THE DISTRICT'S RESPONSIBILITY SHALL BE THE IRRIGATION MAIN AND WHERE NEEDED THE SLEEVE OR TEE FOR TAPPING THE IRRIGATION MAIN.
3. IRRIGATION MAIN SHOWN ON PROPERTY OWNER'S SIDE OF STREET.
4. SHOULD ANY SITUATION ARISE OTHER THAN SHOWN, CONTACT THE DISTRICT REPRESENTATIVES.
5. A PRESSURE REDUCING VALVE IS REQUIRED BEFORE THE METER IF STATIC PRESSURE IS GREATER THAN 95 PSI.

REV. DATE

06/12




MERIDIAN METROPOLITAN DISTRICT

IRRIGATION LINE, STOP BOX AND OUTSIDE METER

INSTALLATION FOR 3/4" AND 1" SETS

WS-25




NOTES:

1. ALL METER PITS LOCATED IN CONCRETE, WHEN ALLOWED BY THE DISTRICT, SHALL HAVE A CAST IRON DOME AND COVER.
2. METERS INSTALLED IN PITS THAT ARE IN PARKING OR ROADWAYS, WILL REQUIRE THE INSTALLATION OF A REMOTE WIRE AND CONDUIT. METERS INSTALLED IN LANDSCAPED AREAS WILL REQUIRE THAT A 2" HOLE BE PROVIDED IN THE CENTER OF THE LID AT THE OWNERS EXPENSE FOR THE INSTALLATION OF A REMOTE SENSING UNIT.
3. SHOULD ANY SITUATION ARISE OTHER THAN SHOWN, CONTACT DISTRICT REPRESENTATIVES.

REV. DATE		MERIDIAN METROPOLITAN DISTRICT	
05/13		METER PIT FOR $\frac{3}{4}$ " AND 1" METERS (TANDEM SETTER & IRRIGATION ONLY)	WS-26

W:\TECHCENTER\projects\200606-24\wg\B\COCS\Utility_Design\15-26 Meter Pit for 0.75 and 1 inch tandem meter.dwg, 5/10/2013 8:58:59 AM, mcedric, 1:1





NOTES:

1. ALL METER PITS LOCATED IN CONCRETE, WHEN ALLOWED BY THE DISTRICT, SHALL HAVE A CAST IRON DOME & COVER.
2. METERS INSTALLED IN PITS THAT ARE IN PARKING OR ROADWAYS, WILL REQUIRE THE INSTALLATION OF A REMOTE WIRE AND CONDUIT. METER PITS INSTALLED IN LANDSCAPED AREAS WILL REQUIRE TO BE CONSTRUCTED AS SHOWN AT THE OWNERS EXPENSE FOR THE INSTALLATION OF A REMOTE SENSING UNIT.
3. JOINTS INSIDE METER VAULT AND CONNECTIONS TO VALVES SHALL BE THREADED OR FLANGED. METER SHALL BE FLANGED OR THREADED W/BRASS COMPANION FLANGES. DUCTILE IRON PIPE OR TYPE K COPPER PIPE SHALL BE USED 5' EITHER SIDE OF VAULT.
4. SHOULD ANY SITUATION ARISE OTHER THAN SHOWN, CONTACT DISTRICT REPRESENTATIVES.
5. A PRESSURE REDUCING VALVE IS REQUIRED BEFORE THE METER IF STATIC PRESSURE IS GREATER THAN 95 PSI.

W:\TECHCENTER\proj\050606-34\wg\BLC\OS\Utility Drawings\WS-27 Outside Setting for Irrigation Meter in Manhole.dwg, 5/10/2013 9:05:07 AM, Inrbed, 1:1

REV. DATE 05/13		MERIDIAN METROPOLITAN DISTRICT OUTSIDE SETTING FOR 1 1/2" AND 2" IRRIGATION METER IN MANHOLE	WS-27
--------------------	--	---	--------------



NOTES:

1. BACKFLOW PREVENTER MAY BE REQUIRED UPON RECOMMENDATION OF DISTRICT.
2. A MINIMUM OF 6" OF $\frac{3}{4}$ " CRUSHED ROCK SHALL BE PLACED UNDER THE ENTIRE VAULT (SEE WS-29).
3. WHEN METER VAULT AND/OR CURB STOP BOX IS LOCATED IN LANDSCAPED AREAS A 6" CONCRETE COLLAR IS REQUIRED AROUND THE MANHOLE AND THE GATE VALVE.
4. VAULT MAY BE ROUND IF PRIOR APPROVAL FROM THE DISTRICT IS RECEIVED.
5. A PRESSURE REDUCING VALVE IS REQUIRED BEFORE THE METER IF STATIC PRESSURE IS GREATER THAN 95 PSI.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

STANDARD SETTING FOR 3" & 4" IRRIGATION METER VAULT

WS-28



NOTES:

1. A MINIMUM OF 6" OF $\frac{3}{4}$ " CRUSHED ROCK SHALL BE PLACED UNDER THE ENTIRE VAULT.
2. WHEN METER VAULT AND/OR CURB STOP BOX IS LOCATED IN LANDSCAPED AREAS A 6" CONCRETE COLLAR IS REQUIRED AROUND THE MANHOLE AND THE GATE VALVE (SEE WS-28 FOR ADDITIONAL DETAILS).
3. RAMNEK ALL EXTERIOR JOINTS.

REV. DATE
06/12





MERIDIAN METROPOLITAN DISTRICT

STANDARD FOR 3" & 4" IRRIGATION METER VAULT

WS-29

I:\TECHCENTER\projects\2008\06-24\Map\BLOCCK\BUILTY\Drawings\WS-29 Standard 3 and 4 inch irrigation meter vault.dwg, 11/13/2012 12:32:52 PM, mmerzak, 1:1



- | | |
|---------------------------------|-----------------------------|
| ① BALL VALVE WITH HANDLE | ⑤ CUSTOM SETTER |
| ② METER | ⑥ TWO BOLT ADAPTOR |
| ③ LOK-PAK COUPLING | ⑦ LOCKING WING VALVE |
| ④ COMPRESSION OR FLARED FITTING | ⑧ CUSTOM SETTER ANGLE VALVE |
| | ⑨ PRESSURE REDUCING VALVE |

NOTES:

- METERS INSTALLED IN PITS THAT ARE IN PARKING OR ROADWAYS, WILL REQUIRE THE INSTALLATION OF A REMOTE WIRE AND CONDUIT. METERS PITS INSTALLED IN LANDSCAPED AREAS WILL REQUIRE THAT A 2" HOLE BE PROVIDED IN THE CENTER OF THE MANHOLE COVER AT THE OWNERS EXPENSE FOR THE INSTALLATION OF A REMOTE SENSING UNIT.
- FOR AN INSIDE INSTALLATION, REFER TO DETAIL WS-12. WHEN USING CUSTOM SETTER FOR AN OUTSIDE INSTALLATION, REFER TO DETAIL WS-21 (DOMESTIC SERVICE).
- FOR AN OUTSIDE IRRIGATION INSTALLATION, REFER TO DETAIL WS-31.
- BACK FLOW PREVENTER MAY BE REQUIRED BY THE DISTRICT.
- A PRESSURE REDUCING VALVE IS REQUIRED BEFORE THE METER IF STATIC PRESSURE IS GREATER THAN 95 PSI.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

METER SETTING FOR INSIDE OR OUTSIDE INSTALLATION
WITH CUSTOM SETTER (1 1/2" OR 2")

WS-30



NOTES:

1. TYPE OF METER TO BE DETERMINED BY MERIDIAN METROPOLITAN DISTRICT.
2. READOUT IN GPM AND DAILY TOTALIZER.
3. REMOTE READ OUT LOCATION TO BE DETERMINED BY THE DISTRICT.
4. CONNECTION CABLES TO BE INSTALLED IN 3" SCH. 40 PVC WITH NO SPLICES BURIED WITH 3' MIN. COVER.
5. RADIO REMOTE READOUT-K SERIES 900 MHZ SERIAL READOUT (FIELD SIGNAL CONFIRMATION REQUIRED PRIOR TO EQUIPMENT ORDER).

REV. DATE

05/13



MERIDIAN METROPOLITAN DISTRICT

4" METER VAULT

WS-31

IT\ECENTER\proj\050606-34\wg\GCS\Utility Drawings\S-2 8 inch meter vault.dwg, 5/10/2013 9:15:40 AM, rtwad, 1:1

REV. DATE


05/13



MERIDIAN METROPOLITAN DISTRICT



8" METER VAULT

WS-32



NOTES:

1. TYPE OF METER TO BE DETERMINED BY MERIDIAN METROPOLITAN DISTRICT.
2. REMOTE READ OUT LOCATION TO BE DETERMINED BY THE DISTRICT.
3. CONNECTION CABLES TO BE INSTALLED IN 3" SCH. 40 PVC WITH NO SPLICES BURIED WITH 3' MIN. COVER.
4. RADIO REMOTE READOUT-K SERIES 900 MHZ SERIAL READOUT (FIELD SIGNAL CONFIRMATION REQ. PRIOR TO EQUIPMENT ORDER).



REV. DATE


05/13



MERIDIAN METROPOLITAN DISTRICT


SANITARY SEWER MAIN BEDDING DETAIL

SM-1




**SANITARY SEWER MAIN
CROSSING OVER ANOTHER MAIN**

NOT TO SCALE



① PIPE BEDDING -
SQUEEGEE OR $\frac{3}{4}$ " ROCK



**SANITARY SEWER MAIN
CROSSING UNDER ANOTHER MAIN**

NOT TO SCALE

NOTES:

1. ENCASE PIPE PER DETAIL SM-3.
2. ANY EXISTING SEWER DAMAGED DURING INSTALLATION MUST BE REPLACE WITH PVC.
3. DISTRICT APPROVED FLEX COUPLING SHALL BE USED: FERNCO 5000 SERIES REPAIR COUPLING, MISSION FLEX-SEAL ADJUSTABLE REPAIR COUPLING, ONSET SHEAR GUARD.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

SANITARY SEWER MAIN CROSSING DETAIL

SM-2



PIPE INSIDE DIAMETER	NUMBER OF LONGITUDINAL BARS & LOCATION
8"	4 - NO. 4 BARS; 2 EACH SIDE
10"	8 - NO. 4 BARS; 3 EACH SIDE
12"	8 - NO. 4 BARS; 3 EACH SIDE
15"	8 - NO. 4 BARS; 3 EACH SIDE
18"	8 - NO. 4 BARS; 3 EACH SIDE
21"	12 - NO. 4 BARS; 4 EACH SIDE
24"	12 - NO. 4 BARS; 4 EACH SIDE
27"	12 - NO. 4 BARS; 4 EACH SIDE
30"	12 - NO. 4 BARS; 4 EACH SIDE
33"	12 - NO. 4 BARS; 4 EACH SIDE
36"	12 - NO. 4 BARS; 4 EACH SIDE

NOTES:

1. ALL CONCRETE SHALL DEVELOP 4000 PSI COMPRESSIVE STRENGTH AFTER 28 DAYS.
2. ANY EXISTING SEWER DAMAGED DURING INSTALLATION MUST BE REPLACE WITH PVC.
3. DISTRICT APPROVED FLEX COUPLING SHALL BE USED: FERNCO 5000 SERIES REPAIR COUPLING, MISSION FLEX-SEAL ADJUSTABLE REPAIR COUPLING, ONSET SHEAR GUARD.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT


CONCRETE ENCASMENT DETAIL

SM-3



PLAN VIEW

NOT TO SCALE



SECTION A - A

NOT TO SCALE

- ① RING AND COVER SET TO PARALLEL FINISHED SURFACE. MANHOLES PLACED IN THE "OPEN SPACE" AREAS SHALL BE INSTALLED WITH THE RING AND COVER AT AN ELEVATION THAT IS 6" ABOVE FINAL GRADE WITH A COLLAR OF CONCRETE.
- ② RING AND COVER GRADE ADJUSTMENT - PRECAST CONCRETE RINGS (18" MAXIMUM). HDPE RINGS MAY BE ALLOWED WITH PRIOR DISTRICT APPROVAL.
- ③ ECCENTRIC CONE.
- ④ MANHOLE BARREL RISER SECTION. REINFORCEMENT PER ASTM C 478.
- ⑤ FOR PVC PIPE, USE A WATER STOP GASKET PER MANUFACTURER'S SPECIFICATION.
- ⑥ JOINT SEALANT - RAMNEK SEALING COMPOUND BOTH SIDES. COMPOUND TO EXTRUDE INTO MH AND BE TRIMMED OFF.
- ⑦ #4 REINFORCING BAR ON 12" CENTER - BOTH WAYS.
- ⑧ BASE IS CAST-IN-PLACE UNLESS PRIOR APPROVAL IS GRANTED BY THE DISTRICT. MINIMUM DROP ACROSS THE MANHOLE IS 0.2' FOR THROUGH MAINS AND 0.3' FOR 90° CONNECTIONS. MANHOLE I.D. IS 4' FOR 18" AND LESS PIPES; MANHOLE I.D. IS 5' FOR 20" - 30" PIPES; MANHOLE I.D. IS 6' FOR 33" AND UP PIPES.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

STANDARD MANHOLE DETAIL

SM-4



NOTES:

1. GROUT FILL IS USED TO SHAPE INVERTS. SIDE SLOPES SHALL BE 1"/FOOT WITH A 1" MINIMUM DROP.
2. MANHOLES BASES, RISERS, LIDS, ETC. TO BE REINFORCED PER SM-4. MANHOLE I.D. IS 4' FOR 18" & LESS PIPES; MANHOLE I.D. IS 5' FOR 20" - 30" PIPES; MANHOLE I.D. IS 6' FOR 33" AND UP PIPES.
3. MINIMUM DROP ACROSS THE MANHOLE IS 0.2' FOR THROUGH MAINS & 0.3' FOR 90° CONNECTIONS.
4. A LOK GASKET PER ASTM RUBBER GASKET SPECIFICATION C443, CAST INTEGRALLY IN MANHOLE WALL AND LOCATED AS REQUIRED. JOINT ALLOWS 10° DEFLECTION OR EQUIVALENT.
5. MUST HAVE PRIOR APPROVAL FROM THE DISTRICT BEFORE INSTALLATION. CAST-IN-PLACE BASE IS THE DISTRICT STANDARD. SEE SM-4 FOR ADDITIONAL DETAILS.
6. RING & COVER SET TO PARALLEL THE FINISHED SURFACE. MANHOLES PLACED IN THE "OPEN SPACE" AREAS SHALL BE INSTALLED WITH THE RING & COVER AT AN ELEVATION THAT IS 6" ABOVE FINAL GRADE WITH A CONCRETE COLLAR.
7. RING & COVER GRADE ADJUSTMENT - PRECAST CONCRETE RINGS (18" MAXIMUM). HDPE RINGS MAY BE ALLOWED WITH PRIOR DISTRICT APPROVAL.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

STANDARD MANHOLE DETAIL - PRECAST BASE

SM-5



PLAN VIEW
NOT TO SCALE

NOTES:

1. MANHOLE BASE TO HAVE SHAPED INVERTS. BASE TO BE A MONOLITHIC CONCRETE POUR.
2. MANHOLES BASES, RISERS, LIDS, ETC. TO BE REINFORCED PER SM-4.
3. SLOPES SHALL BE 1"/FOOT WITH A 1" MINIMUM DROP.
4. BASE IS CAST-IN-PLACE UNLESS PRIOR APPROVAL IS GRANTED BY THE DISTRICT. MINIMUM DROP ACROSS THE MANHOLE IS 0.2' FOR THROUGH MAINS AND 0.3' FOR 90° CONNECTIONS.

REV. DATE

06/12




MERIDIAN METROPOLITAN DISTRICT


STANDARD MANHOLE BASE DETAIL

SM-6

#4 REBAR @
12 INCH ON-CENTER



WATER STOP
GASKET - TYP.
(SEE SM-4)



WATER STOP
GASKET - TYP.
(SEE SM-4)

FLOW

FLOW

NOTES:

1. THE RE-BAR BASKET MAY BE EITHER ROUND OR SQUARE.
2. MANHOLE RISERS, LIDS, ETC. TO BE REINFORCED PER SM-4.
4. BASE IS CAST-IN-PLACE UNLESS PRIOR APPROVAL IS GRANTED BY THE DISTRICT. MINIMUM DROP ACROSS THE MANHOLE IS 0.2' FOR THROUGH MAINS AND 0.3' FOR 90° CONNECTIONS.

REV. DATE

06/12




MERIDIAN METROPOLITAN DISTRICT

STANDARD MANHOLE BASE REBAR BASKET

SM-7

#4 REBAR @
12 INCH ON-CENTER

WATER STOP
GASKET - TYP.
(SEE SM-4)



NOTES:

1. THE RE-BAR BASKET MAY BE EITHER ROUND OR SQUARE.
2. MANHOLE RISERS, LIDS, ETC. TO BE REINFORCED PER SM-4.
4. BASE IS CAST-IN-PLACE UNLESS PRIOR APPROVAL IS GRANTED BY THE DISTRICT. MINIMUM DROP ACROSS THE MANHOLE IS 0.2' FOR THROUGH MAINS AND 0.3' FOR 90° CONNECTIONS.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

STANDARD MANHOLE BASE REBAR BASKET


SM-8




THROUGH PIPE

THROUGH PIPE
ONE COLLECTION LINE


THROUGH PIPE
TWO COLLECTION LINE




INTERMEDIATE ANGLE
 $\alpha = 30^\circ$



SHARP ANGLE
 $\alpha = 90^\circ$



INTERMEDIATE ANGLE
 $\alpha = 45^\circ$



OPPOSED LATERALS

NOTES:

1. C.M.H. IS CENTER OF MANHOLE.
2. BASE IS CAST-IN-PLACE UNLESS PRIOR APPROVAL IS GRANTED BY THE DISTRICT. MINIMUM DROP ACROSS THE MANHOLE IS 0.2' FOR THROUGH MAINS AND INTERMEDIATE ANGLES; DROP ACROSS THE MANHOLE IS 0.3' FOR 90° (SHARP ANGLES AND OPPOSED LATERALS).

REV. DATE



06/12



MERIDIAN METROPOLITAN DISTRICT

TYPICAL BASE AND DEFLECTOR DETAILS



SM-9



NOTES:

1. TIE-INS SHALL ONLY BE PERMITTED THROUGH BASE WALL.
2. STEPS INSTALLED OVER DOWNSTREAM INVERT OF MANHOLE.
3. A WATER STOP GASKET SHALL BE INSTALLED PER MANUFACTURER'S SPECIFICATIONS.
4. MINIMUM DROP ACROSS THE MANHOLE IS 0.2' FOR THROUGH MAINS & 0.3' FOR 90° CONNECTIONS.

REV. DATE		MERIDIAN METROPOLITAN DISTRICT	SM-10
06/12			
		MANHOLE INVERT TIE IN DETAIL	




NOTES:

1. REQUIRED IN MANHOLES WHERE THE DEPTH MEASURED FROM THE RING AND COVERT TO THE INVERT EXCEEDS 20 FEET.
2. VERTICALLY CENTER FLATTOP PLATFORM BETWEEN RING AND COVER AND MANHOLE INVERT.


<p>REV. DATE</p> <p>06/12</p>		<p>MERIDIAN METROPOLITAN DISTRICT</p> <p>MANHOLE PLATFORM DETAIL</p>	<p>SM-11</p>
-------------------------------	---	---	---------------------

I:\TECHCENTER\projects\2006\06-24\mg\BLOCCK\BUNNY\Drawings\SM-11 Manhole Platform Detail.dwg, 11/13/2012 1:02:07 PM, mmerquez, 11



BRACKET DETAIL

MANUFACTURE BRACKET FROM 3/8" STAINLESS STEEL
 ALL BRACING MATERIALS SHALL BE CONSTRUCTED USING STAINLESS STEEL



NOTES:

1. MANHOLE SIZE VARIES WITH SIZE OF THE MAINLINE: 8" - 10" MAINLINE = 5' DIA. MANHOLE; 12" - 15" MAINLINE = 6' DIA. MANHOLE; MAINLINES LARGER THAN 15" = 7' DIA. MANHOLE. STEPS INSTALLED OVER DOWNSTREAM INVERT OF MANHOLE. EPOXY COAT INTERIOR OF MANHOLE.
2. CONCRETE COLLAR TO BE POURED AROUND BOTH RING AND LOCKING CLEANOUT.
3. AN ECCENTRIC CONE MAY BE USED WITH PRE-CONSTRUCTION APPROVAL BY THE MERIDIAN METROPOLITAN DISTRICT.

REV. DATE


06/12




MERIDIAN METROPOLITAN DISTRICT

INSIDE DROP MANHOLE CONSTRUCTION DETAIL


SM-12



DETAIL FOR M.A. INDUSTRIES STEP, OR APPROVED EQUAL



SECTION A-A



TYPICAL STEP INSTALLATION

NOTES:

1. ALL WORK SHALL BE DONE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS APPLICABLE TO THE PROJECT.
2. CAST IRON STEPS WILL NOT BE PERMITTED.

REV. DATE


06/12




MERIDIAN METROPOLITAN DISTRICT

STANDARD STEP FOR MANHOLES


SM-13




HALF PLAN



LETTERING DETAIL



LIFTING NOTCH DETAIL



NOTES:

1. COVER SHALL BE THE DISTRICT STANDARD PATTERN. THE CASTING SHALL BE OF GRAY CAST IRON, ASTM DESIGNATION A48 CLASS 35B. CASTING SHALL NOT BE PAINTED OR DIPPED.
2. TOTAL WEIGHT SHALL BE A MINIMUM OF 400 LBS (LID WEIGHT OF 165 LBS MIN.), CAST IRON ONLY.
3. ALL BEARING SURFACES SHALL BE MACHINED.
4. CASTINGS SHALL BE CLEAN, FREE OF FUSED SAND & REASONABLY SMOOTH. THERE SHALL BE NO PROMINENT BLOW HOLES, NO CRACKS OR FISSURES, AND NO OBSERVED INCOMPLETE FILLING OF THE MOLD.

REV. DATE


06/12




MERIDIAN METROPOLITAN DISTRICT

24" MANHOLE COVER DETAIL


SM-14




HALF PLAN



LETTERING DETAIL



LIFTING NOTCH DETAIL



NOTES:

1. COVER SHALL BE THE DISTRICT STANDARD PATTERN. THE CASTING SHALL BE OF GRAY CAST IRON, ASTM DESIGNATION A48 CLASS 35B. CASTING SHALL NOT BE PAINTED OR DIPPED.
2. TOTAL WEIGHT SHALL BE A MINIMUM OF 400 LBS (LID WEIGHT OF 165 LBS MIN.), CAST IRON ONLY.
3. ALL BEARING SURFACES SHALL BE MACHINED.
4. CASTINGS SHALL BE CLEAN, FREE OF FUSED SAND & REASONABLY SMOOTH. THERE SHALL BE NO PROMINENT BLOW HOLES, NO CRACKS OR FISSURES, AND NO OBSERVED INCOMPLETE FILLING OF THE MOLD.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

30" MANHOLE COVER DETAIL

SM-15



- NOTES:**
 1. SEE SM-4 & SM-5 FOR MANHOLE DETAILS.
 2. SEE WM-6 FOR THRUST BLOCK DETAILS.


REV. DATE
06/12




MERIDIAN METROPOLITAN DISTRICT
 DEAD END MANHOLE SERVICE CONNECTION DETAIL

SM-16

I:\TECHNICAL\projects\2008\06-24\MD\BLOC\BUI\DWG\SM-16 Dead End Manhole Service Connection Detail.dwg, 11/13/2012, 10:42:17 AM, miquiz, 1:1



PLAN



ELEVATION

NOTES:

1. SEE WM-17 & WM-18 FOR OPERATOR SHAFT AND EXTENSION GUIDE DETAIL.

REV. DATE

06/12




MERIDIAN METROPOLITAN DISTRICT

FORCE MAIN PLUG VALVE MANHOLE DETAIL

SM-17


I:\TECHCENTER\projects\2008\06-24\MC\BLOC\BUIL\Drawings\SM-17 Force Main Plug Valve Manhole Detail.dwg, 11/13/2012 10:45:27 AM, mmanraz, 11

SEE DISTRICT
STANDARDS FOR
MINIMUM SLOPE
AND TYPE OF PIPE



1/8° BEND CONNECTION TO WYE

SEE DISTRICT
STANDARDS FOR
MINIMUM SLOPE
AND TYPE OF PIPE



1/8° BEND CONNECTION TO A TAPPING SADDLE

NOTES:

1. SANITARY SEWER MAIN - PIPE BEDDING IS EITHER SQUEEGEE OR 3/4" CRUSHED ROCK.
2. SEE SM-1 FOR ADDITIONAL BEDDING DETAILS.

REV. DATE


06/12




MERIDIAN METROPOLITAN DISTRICT

SANITARY SEWER SERVICE TAPPING DETAIL

SS-1



TYPE A



TYPE B

NOTES:

1. TYPE "A" ELEMENTS ARE TYPICAL FOR ALL TYPES UNLESS SPECIFICALLY NOTED OTHERWISE.
2. ALL LATERALS SHALL BE LOCATED 10' MINIMUM DISTANCE FROM DOWNHILL PROPERTY LINE OF THE SERVICE SIDE OF THE LOT, UNLESS OTHERWISE APPROVED BY THE DISTRICT PRIOR TO INSTALLATION.
3. ALL SEWER LATERAL CONNECTIONS SHALL BE TYPE "A" AND SHALL BE CONSTRUCTED ON A STRAIGHT LINE AND GRADE BETWEEN CONTROL POINTS EXCEPT AS OTHERWISE INDICATED ON THE APPROVED PROJECT PLANS.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

SANITARY SERVICE CONNECTION

SS-2



NOTES:

1. SEWER SERVICE LINES (INDIVIDUAL TRENCH) SHALL BE LOCATED A MAXIMUM OF 1.5' ON EITHER SIDE OF THE CENTER LINE OF THE LOT.
2. FOR JOINT TRENCH INSTALLATIONS, SEWER SERVICE LINES SHALL BE LOCATED IN ACCORDANCE WITH WS-1.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

SANITARY SEWER SERVICE LOCATION ONLY
(CENTER LOT)

SS-3



LAMP HOLE COVER DETAIL

NOTES:

1. COVER SHALL HAVE A LOCKING LID MARKED "SEWER".
2. TYLER SERIES 6855 SLIP TYPE TOP SECTION, D&L SUPPLY SERIES M8056 OR EQUAL.
3. INSIDE DIAMETER = 6 1/8".

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

IN-LINE SANITARY SEWER CLEANOUT
(4" & 6")

SS-4



NOTES:

1. SECONDARY COMPARTMENT HAS VOLUME EQUAL TO 1/3 OF TOTAL CAPACITY.
2. ALL PIPE AND FITTINGS SHALL BE SOLVENT WELDED SCHEDULE 40 P.V.C. MIN. 3" DIA. WITHIN TRAP.
3. WALL AND BOTTOM REINFORCED THROUGHOUT WITH 2X16 #10 REMESH.
4. COVERS TO BE REINFORCED LONGITUDINALLY WITH NO. 6 REBAR ON 6" CENTERS, NO. 4 REBAR ON 6" CENTERS WIDTHWISE, AND NO. 8 REBAR DIAGONALLY AROUND ACCESS HOLES.
5. CLEAN OUT SHALL BE PVC SCREW PLUG
6. VENT PIPE MAY BE CAST IRON OR PVC SCHEDULE 40, TO A POINT 6" ABOVE GROUND.
7. MANHOLE RING AND COVER SHALL BE 24" DENVER HEAVY OR EQUAL.
8. CHECK WITH SUPPLIER FOR EXACT DIMENSIONS.
9. NO BOLT TIE DOWN COVER ALLOWED WITHOUT PERMISSION FROM MERIDIAN METROPOLITAN DISTRICT.
10. CAPACITY RATED FOR LARGE COMPARTMENT ONLY.
11. ALL BRACING SHALL BE CONSTRUCTED WITH STAINLESS STEEL MATERIALS.

WATER CAPACITY APPROX. GALLONS	DIMENSIONS IN INCHES			
	C	D	E	F
1565	40	50	48	62
1800	46	56	54	68
2035	52	62	60	74
2505	64	74	72	86
2975	76	86	84	98
3210	82	92	90	104
3445	88	98	96	110

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

SAND AND OIL INTERCEPTOR

SS-5



NOTES:

1. SECONDARY COMPARTMENT HAS VOLUME EQUAL TO $\frac{1}{3}$ OF TOTAL CAPACITY.
2. ALL PIPE AND FITTINGS SHALL BE SOLVENT WELDED SCHEDULE 40 P.V.C. MIN. 3" DIA. WITHIN TRAP.
3. WALL AND BOTTOM REINFORCED THROUGHOUT WITH 2X16 $\frac{9}{10}$ REMESH.
4. COVERS TO BE REINFORCED LONGITUDINALLY WITH NO. 6 REBAR ON 6" CENTERS, NO. 4 REBAR ON 6" CENTERS WIDTHWISE, AND NO. 8 REBAR DIAGONALLY AROUND ACCESS HOLES.
5. CLEAN OUT SHALL BE PVC SCREW PLUG
6. VENT PIPE MAY BE CAST IRON OR PVC SCHEDULE 40, TO A POINT 6" ABOVE GROUND.
7. MANHOLE RING AND COVER SHALL BE 24" DENVER HEAVY OR EQUAL.
8. CHECK WITH SUPPLIER FOR EXACT DIMENSIONS.
9. NO BOLT TIE DOWN COVER ALLOWED WITHOUT PERMISSION FROM MERIDIAN METROPOLITAN DISTRICT.
10. CAPACITY RATED FOR LARGE COMPARTMENT ONLY.
11. ALL BRACING SHALL BE CONSTRUCTED WITH STAINLESS STEEL MATERIALS.

WATER CAPACITY APPROX. GALLONS	DIMENSIONS IN INCHES					
	A	B	C	D	E	F
320	48	72	22	30	44	24
500	48	72	36	46	44	24
780	48	96	40	48	62	32
1060	72	102	34	42	56	34

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

SAND AND OIL INTERCEPTOR

SS-6



NOTES:

1. SECONDARY COMPARTMENT HAS VOLUME EQUAL TO $\frac{1}{3}$ OF TOTAL CAPACITY.
2. ALL PIPE AND FITTINGS SHALL BE SOLVENT WELDED SCHEDULE 40 P.V.C. MIN. 3" DIA. WITHIN TRAP.
3. WALL AND BOTTOM REINFORCED THROUGHOUT WITH 2X16 $\frac{9}{10}$ REMESH.
4. COVERS TO BE REINFORCED LONGITUDINALLY WITH NO. 6 REBAR ON 6" CENTERS, NO. 4 REBAR ON 6" CENTERS WIDTHWISE, AND NO. 8 REBAR DIAGONALLY AROUND ACCESS HOLES.
5. CLEAN OUT SHALL BE PVC SCREW PLUG
6. VENT PIPE MAY BE CAST IRON OR PVC SCHEDULE 40, TO A POINT 6" ABOVE GROUND.
7. MANHOLE RING AND COVER SHALL BE 24" DENVER HEAVY OR EQUAL.
8. CHECK WITH SUPPLIER FOR EXACT DIMENSIONS.
9. NO BOLT TIE DOWN COVER ALLOWED WITHOUT PERMISSION FROM MERIDIAN METROPOLITAN DISTRICT.
10. CAPACITY RATED FOR LARGE COMPARTMENT ONLY.
11. ALL BRACING SHALL BE CONSTRUCTED WITH STAINLESS STEEL MATERIALS.

WATER CAPACITY APPROX. GALLONS	DIMENSIONS IN INCHES			
	C	D	E	F
1565	40	50	48	62
1800	46	56	54	68
2035	52	62	60	74
2505	64	74	72	86
2975	76	86	84	98
3210	82	92	90	104
3445	88	98	96	110

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

GREASE INTERCEPTOR

SS-7



NOTES:

1. SECONDARY COMPARTMENT HAS VOLUME EQUAL TO $\frac{1}{3}$ OF TOTAL CAPACITY.
2. ALL PIPE AND FITTINGS SHALL BE SOLVENT WELDED SCHEDULE 40 P.V.C. MIN. 3" DIA. WITHIN TRAP.
3. WALL AND BOTTOM REINFORCED THROUGHOUT WITH 2X16 $\frac{9}{10}$ REMESH.
4. COVERS TO BE REINFORCED LONGITUDINALLY WITH NO. 6 REBAR ON 6" CENTERS, NO. 4 REBAR ON 6" CENTERS WIDTHWISE, AND NO. 8 REBAR DIAGONALLY AROUND ACCESS HOLES.
5. CLEAN OUT SHALL BE PVC SCREW PLUG
6. VENT PIPE MAY BE CAST IRON OR PVC SCHEDULE 40, TO A POINT 6" ABOVE GROUND.
7. MANHOLE RING AND COVER SHALL BE 24" DENVER HEAVY OR EQUAL.
8. CHECK WITH SUPPLIER FOR EXACT DIMENSIONS.
9. NO BOLT TIE DOWN COVER ALLOWED WITHOUT PERMISSION FROM MERIDIAN METROPOLITAN DISTRICT.
10. CAPACITY RATED FOR LARGE COMPARTMENT ONLY.
11. ALL BRACING SHALL BE CONSTRUCTED WITH STAINLESS STEEL MATERIALS.

WATER CAPACITY APPROX. GALLONS	DIMENSIONS IN INCHES					
	A	B	C	D	E	F
320	48	72	22	30	44	24
500	48	72	36	46	44	24
780	48	96	40	48	62	32
1060	72	102	34	42	56	34

REV. DATE



06/12



MERIDIAN METROPOLITAN DISTRICT

GREASE INTERCEPTOR

SS-8



REV. DATE

06/12



MERIDIAN METROPOLITAN DISTRICT

WASTE METERING MANHOLE

SS-9

FLUME DESIGN CRITERIA FOR WASTE METERING MANHOLE

FLUME										MANHOLE SIZE ID	SLOPE UPSTREAM
MAXIMUM DISCHARGE			HEAD	MODEL	DIMENSIONS (INCHES)						
GPM	MGD	CFS	INCHES	-	D	D-2	R	H	Z	MINIMUM	MAXIMUM
52	0.075	0.116	2.90	PBF-4	4	2	0.67	6	17	6' Dia.	2.4
165	0.238	0.368	4.70	PBF-6	6	2	1.00	8	25	6' Dia.	2.2
343	0.495	0.765	6.30	PBF-8	8	3	1.33	10	33	6' Dia.	2.0
603	0.870	1.345	7.90	PBF-10	10	4	1.67	12	41	6' Dia.	1.8
936	1.350	2.088	9.40	PBF-12	12	6	2.00	14	49	6' Dia.	1.6
1648	2.377	3.676	11.80	PBF-15	15	7.5	2.50	17	61	6' Dia.	1.5
2614	3.770	5.831	14.20	PBF-18	18	9	3.00	20	73	7.5' Dia.	1.4

REV. DATE

06/12



MERIDIAN METROPOLITAN DISTRICT

FLUME DESIGN CRITERIA

SS-9A

CONTROL MANHOLE NOTES

STRUCTURE:

1. SHAPE AND SMOOTH MANHOLE INVERTS BY FORMING OR SHAPING WITH CEMENT MORTAR.
2. ALL PRECAST MANHOLE SECTION, BASES, FLAT TOPS, BARRELS, REDUCERS, ETC., SHALL CONFORM TO ASTM, C-478, AND THESE STANDARD SPECIFICATIONS.
3. REINFORCING IN BASE REQUIRED FOR 6' & 7.5" DIAMETER MANHOLES. THE OWNER SHALL BE RESPONSIBLE FOR STRUCTURAL REQUIREMENTS UNDER THE SPECIFIC LOADING CONDITIONS, (DEAD LOAD PLUS LIVE LOAD OR H-20 FOR TRAFFIC).
4. MANHOLE RING, COVER AND LEVELING RINGS SHALL BE SET IN A FILL BED OF MORTAR.
5. ECCENTRIC CONE SECTIONS MAY BE USED IN LIEU OF FLAT TOP SECTIONS, PROVIDED COVER OVER TOP OF PIPE IS GREATER THAN 4.5 FEET.
6. FLEXIBLE PLASTIC SEALANT IS REQUIRED IN ALL JOINTS.
7. VENTILATOR MAY BE REQUIRED; DISTRICT ENGINEER SHALL DECIDE WHEN THIS IS NECESSARY, AND APPROVE METHOD OF PROVIDING VENTILATION.

FLUME:

1. THE FLUME SHALL BE A PALMER-BOWLUS FLUME, WITH INTEGRAL APPROACH SECTION, OR APPROVED EQUAL.
2. IT IS SUGGESTED THAT THE OWNER PLACE CONCRETE FOR MANHOLE BENCH IN TWO POURS.
 - (a) POUR BENCH, LEAVING ADEQUATE "BLOCK OUT" AREA TO FIT FLUME.
 - (b) GROUT FLUME INTO "BLOCK OUT" AT EXISTING OR NEW SEWER LINE SLOPE.
3. CONSTRUCTION OF A BYPASS CHANNEL FOR FLUME SHALL BE AT THE OWNER'S OPTION, THIS CAN BE ACCOMPLISHED IN POUR (a). THIS TYPE OF CONSTRUCTION WILL REQUIRE A LARGER STRUCTURE. THE DESIGN OF ANY BYPASS CHANNEL SHALL BE SUCH AS TO INDUCE MINIMUM TURBULENCE IN NORMAL FLUME FLOW CHANNEL.
4. FLUME SELECTION SHALL BE BASED UPON THE FLOW TO BE MEASURED AND NOT UPON THE PIPE SIZE.
5. FLUME SELECTION CALCULATIONS WILL BE SUBMITTED TO DISTRICT ENGINEER FOR CONCURRENCE AS WILL FLUME CALIBRATION CURVES AND DATA.
6. A MOUNTING BRACKET SHALL BE PROVIDED TO SUPPORT THE DISTRICT'S FLOW RECORDING TRANSDUCER. THE BRACKET SHALL BE INSTALLED SO THAT THE TRANSDUCER FACE IS OVER THE CENTER OF THE CHANNEL.

REV. DATE

06/12



MERIDIAN METROPOLITAN DISTRICT

WASTE METERING MANHOLE NOTES

SS-9B

ELECTRIC CONTROL PANEL

1. SHALL BE A MILLTRONICS OCM III - NON-CONTRACTING ULTRASONIC FLOW METER, TWO-WAY COMMUNICATIONS - DATA LOG WITH 2 YEAR HISTORY.
2. CHART RECORDER - FOXBORO 740 SERIES, OR APPROVED EQUAL, WITH 100 PROPERLY SCALED CHARTS FOR THE SIZE OF FLUME UTILIZED.
3. THE TRANSDUCER MOUNTING HARDWARE SHALL BE FIBERGLASS UNISTRUT WITH STAINLESS STEEL ANCHORS & BOLTS. THE MOUNT SHOULD BE DESIGNED TO ALLOW LEVELING OF TRANSDUCER FACE AND OFFERING SOME LATERAL ADJUSTMENTS.
4. CONDUIT FROM MANHOLE PANEL SHALL BE PVC JACKETED GRC, (USING ONLY WIDE RADIUS BENDS).
 REQUIRED (1) 3/4" FOR TRANSDUCER CABLE
 (1) 1" FOR ISCO SAMPLE LINE
 (1) 3/4" SPARE
5. EQUIPMENT ENCLOSURE SHALL BE A NEMA 4, WITH DOUBLE DOOR ACCESS, MOUNTED ON A CONCRETE PAD.
 PANEL SHOULD INCLUDE THE FOLLOWING:
 - ELECTRICAL DISTRIBUTION BOX WITH (6) 20 AMP GFI CIRCUIT BREAKERS.
 - HEATER WITH THERMOSTAT
 - EXHAUST FAN WITH LOUVERS
 - LIGHT
 - UTILITY OUTLETS
 - SIZED ACCORDINGLY TO ACCOMMODATE AN ISCO SAMPLER, MODEL #3700
6. FLUME LENGTH FOR 8" PALMER-BOWLUS WITH APPROACH SECTION,
 (4 x DIAMETER) + 1" e.i. 32" + 1" = 33"

REV. DATE


06/12




MERIDIAN METROPOLITAN DISTRICT

WASTE METERING MANHOLE NOTES

SS-9C



SLED DETAIL



PIPE CASING DETAIL

CARRIER PIPE NOMINAL Ø	CASING PIPE	
	MIN OD	MIN WALL THICKNESS
4"	12"	0.25"
6"	16"	0.3125"
8"	18"	0.3125"
12"	22"	0.375"
16"	28"	0.500"
20"	32"	0.500"

PIPE CASING TABLE

NOTES:

1. CASING LENGTH TO BE SHOWN CLEARLY ON THE APPROVED PLANS.
2. TRENCH LAID CASING SHALL BE DESIGNED AND INSTALLED PER PLANS.
3. BORING AND CASING METHOD AND MATERIALS SHALL BE APPROVED BY THE DISTRICT.
4. SOIL AT THE ENDS OF CASING SHALL BE STABLE AT ALL TIMES.
5. CASING PIPE SHALL BE STRAIGHT, ROUND AND OF NEW MATERIAL.

REV. DATE


August 2012




MERIDIAN METROPOLITAN DISTRICT

BORE CASING DETAIL

D-1



SLED DETAIL



PIPE CASING DETAIL

NOTES:

1. CASING LENGTH TO BE SHOWN CLEARLY ON THE APPROVED PLANS.
2. TRENCH LAID CASING SHALL BE DESIGNED AND INSTALLED PER PLANS.
3. BORING AND CASING METHOD AND MATERIALS SHALL BE APPROVED BY THE DISTRICT.
4. SOIL AT THE ENDS OF CASING SHALL BE STABLE AT ALL TIMES.
5. CASING PIPE SHALL BE STRAIGHT, ROUND AND OF NEW MATERIAL.
6. MUST HAVE PRIOR APPROVAL FROM THE DISTRICT BEFORE CONSIDERING IN APPROVED PLANS.

REV. DATE


August 2012



MERIDIAN METROPOLITAN DISTRICT

DOUBLE BORE CASING DETAIL

D-2



NOTES:

1. LOCATIONS TO BE SHOWN CLEARLY ON THE APPROVED PLANS.
2. IDENTIFICATION MARKS ON POSTS SHALL BE 3"Ø CIRCLES BROKEN IN VERTICAL CENTER (SEE DETAIL) POINTING TO APPURTENANCE, WITH 1" STENCILS INSIDE CIRCLE INDICATING TYPE OF APPURTENANCE (MH, 12" GATE VALVE, ETC) AND THE DISTANCE IN FEET AND INCHES FROM POST.

REV. DATE


August 2012



MERIDIAN METROPOLITAN DISTRICT

REFERENCE POST DETAIL

D-3



NOTE:

1. BAR MATERIAL TO BE ASTM A 240 TYPE 304 OR 316 ($F_y = 30$ KSI MINIMUM).

REV. DATE


August 2012



MERIDIAN METROPOLITAN DISTRICT

ADJUSTABLE SUPPORT DETAIL (STANDARD)

D-4



HEAVY DUTY

NOTE:

1. BAR MATERIAL TO BE ASTM A 240 TYPE 304 OR 316 (Fy = 30 KSI MINIMUM).

REV. DATE

August 2012



MERIDIAN METROPOLITAN DISTRICT


ADJUSTABLE SUPPORT DETAIL (HEAVY DUTY)

D-5

FINISHED GRADE


TIDEFLEX TF-1
SLIP-ON CHECK VALVE

STAINLESS STEEL BAND
OR HALF CLAMPS



6" MIN.

10'



TYPE "L" RIP RAP
LENGTH = 4*PIPE DIA.
WIDTH = 4*PIPE DIA.
DEPTH = 18" MINIMUM

REV. DATE


August 2012



MERIDIAN METROPOLITAN DISTRICT

TIDEFLEX CHECK VALVE DETAIL
FOR DRAIN OUTLET

D-6



TYPICAL SIGN FOR CONCRETE WASHOUT

NOTES:

1. SEE DOUGLAS COUNTY GESC MANUAL SECTION 3.13.5.
2. SIGN SHALL BE CONSTRUCTED OF WEATHER RESISTANT MATERIALS.

REV. DATE


August 2012



MERIDIAN METROPOLITAN DISTRICT

CONCRETE WASHOUT SIGN

D-7



TYPICAL CONSTRUCTION ACCESS SIGN

NOTES:

1. SIGN PER EXHIBIT 9 OF THE MERIDIAN VILLAGE DESIGN CONTROL COMMITTEE MANUAL.
2. SIGN SHALL BE CONSTRUCTED OF WEATHER RESISTANT MATERIALS.

REV. DATE





August 2012



MERIDIAN METROPOLITAN DISTRICT

CONSTRUCTION ACCESS SIGN

D-8



**DETAIL - ENCASEMENT,
ENCASED DUCT BANK SECTIONS**

REINFORCING OF DUCT BANK

PROVIDE REINFORCING STEEL AT THE FOLLOWING LOCATIONS:

1. CROSSING OF ALL ROADS BETWEEN OUTSIDE EASEMENT LINES.
2. CROSSING OF ALL EXISTING AND PLANNED PIPELINES AND DUCTS, TO 10'-0" OF EITHER SIDE.
3. WITHIN 10'-0" OF WATER VALVES, MANHOLES AND VAULTS.
4. AS DETERMINED IN THE FIELD WHERE DAMAGE BY SETTLING MAY OCCUR.
5. REINFORCING STEEL SHALL BE GR-60.

NOTES:

1. CONDUIT SPACING SHALL BE MAINTAINED BY FACTORY MADE DUCT-BANK SPACERS.
2. ALL CONDUIT JOINTS SHALL BE CEMENTED WATERTIGHT.
3. REINFORCING ROD SHALL BE SUPPORTED AWAY FROM EARTH FOR COMPLETE ENCASEMENT.
4. CHANGES IN CONFIGURATION SHALL HAVE ADDITIONAL REINFORCEMENT AND BE APPROVED BY THE MERIDIAN METROPOLITAN DISTRICT PRIOR TO ENCASEMENT.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

DUCT ENCASEMENT SECTIONS

DAS-1



REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

TYPICAL CONTROL CONDUIT MANHOLE

DAS-2



DETAIL - TYPICAL STREET CROSSING SECTION

NOTES:

1. END CONCRETE OF CROSSING STUBS AT WATER EASEMENT AND LEAD WARNING TAPE TO GRADE. EXTEND CONDUIT AND REBAR 1-3 FEET BEYOND CONCRETE.

REV. DATE


06/12



MERIDIAN METROPOLITAN DISTRICT

CONTROL CONDUIT TYPICAL STREET CROSSING

DAS-3



NOTES:

1. ASSEMBLY SHALL BE RATED FOR AASHTO H-10 LOADING. BOX OF REINFORCED PLASTIC MORTAR, CARLON "COM, SOLITE" OR EQUAL.

REV. DATE



06/12



MERIDIAN METROPOLITAN DISTRICT

CONTROL CONDUIT PULL BOX ARRANGEMENT

DAS-4



REV. DATE

06/12



MERIDIAN METROPOLITAN DISTRICT

STREET LIGHTING

STL-1

CONSTRUCTION NOTES: FOR STREET LIGHT ASSEMBLY ONLY

- ① THE POLE DIMENSIONS SHOWN ARE FOR A CENTRECOM 25 FOOT POLE. THE ACTUAL POLE DIMENSIONS WILL VARY TO STANDARD POLE DIMENSIONS OF SPECIFIED MANUFACTURER.
- ② PROVIDE 3 TIES @ 3" ON CENTER @ TOP OF PIER.
- ③ PRECAST CONCRETE POLE UP TO 30 FT. REFERENCE POLE MANUFACTURER FOR BOLT SIZE, LENGTH, AND LOCATION.
- ④ PROVIDE 36" - 3 PIER WITH 12 #6 VERTICAL AND #4 TIES @ 18" ON CENTER.
- ⑤ PROVIDE GROUT CAP TO COVER ALL EXPOSED METAL PARTS

AESTHETIC SPECIFICATION:

CONCRETE POLES:


- STRENGTH: REFER TO SPECS FOR CALCULATIONS TO BE SUBMITTED.
 - MATERIAL: REINFORCED CONCRETE WITH INTERNAL RACEWAY.
 - FORM: SQUARE TAPERED WITH 1" BEVELED CORNERS
 - MOUNTING: TENON ON TOP OF POLE.
 - FINISH: EXPOSED AGGREGATE: PEBBLE TEXTURE, SAND BLASTED OR ACID ETCHED.
 - COLOR: AGGREGATE - SONORA GOLD; CONCRETE - BUFF/SAND BEIGE (REF. CENTRECOM 333)
 - PROTECTIVE COATING: URETHANE
- NOTE: ALSO APPLICABLE TO LANDSCAPE POLES FURNISHED.

LUMINAIRE SUPPORT ARM:

- STEEL OR ALUMINUM (RECTANGULAR)
- PRIME PAINTED FINISH: BAKED ON ENAMEL FINISH OR DURANOTIC FINISH.
- COLOR: (LIGHT AMBER BRONZE) SPEC. REF. KAISER ALUMINUM - KAZCOLOR CHART.
- PROTECTIVE FINISH: URETHANE (PAINTED ONLY)

LUMINAIRE:

- SEE FIXTURE SCHEDULE.



REV. DATE

06/12



MERIDIAN METROPOLITAN DISTRICT

STREET LIGHTING

STL-2