





IDV26

DIRECT VENT GAS FIREPLACE INSERT



Model **Fuel** Input Max. Input Min. FE (P.4.1-15) IDV26N / IDV26NE Natural 30.000 BTU 21.000 BTU

58.82% / 60.27%

IDV26LP / IDV26LPE Propane 30.000 BTU

25.000 BTU 58.82% / 60.27% Convert your wood burning fireplace to gas, for a new standard of warmth, beauty, safety and convenience.

STANDARD FEATURES

- Dual Burner with glowing embers
- Hi/low Millivolt or IPI valve system, will operate during power failures
- Matchless Piezo Ignition
- Decorative Ash Bed
- Ceramic Glass (Heat Radiating)
- On/Off Rocker switch
- Heat activated blower with ariable speed control
- Safety Screen Barrier



Safety Screen Barrier

OPTIONAL FEATURES

Log Set

Fibre Split Oak

Glass Tray with Bronze Glass

Clean View Kit

Black

Surrounds for Clean View

Black

Surround Picture Frame for Clean View

Black

Liners

Porcelain Reflective Liner or Traditional Brick

Wall Mount Thermostat

Standard On/Off or Programmable

Remote Control

On/Off, Thermostat On/Off, Thermostat On/Off modulating













CLEAN VIEW AND SURROUND SIZES (IN.)

IDV26	Width	Height	Depth
126CV1	35 ⁵ /8"	223/4"	$1^{3}/4''$
126CV2	44 ⁵ /8"	26 ⁵ /8"	$1^{3}/4''$
I26CVPF1	35 ⁵ /8"	25 ⁷ /8"	$1^{3}/4''$
I26CVPF2	447/8"	331/2"	$1^{3}/4''$
126S1	42"	271/2"	
I26SU	471/2"	35 ⁵ /8" / 28 ⁵ /8"*	
I26SU	39³/8"	293/4"	
126CV3	35 ⁵ /8"	223/4"	31/2"

^{*}Dimension as a three sided surround

MINIMUM FIREPLACE OPENING (IN.)

	Width	Height	Depth
IDV26	33" / 28"*	19 ¹ /2"	141/4"

^{*}Components In (CV1) 33", Components Out (CV2) 28"

MINIMUM UNIT COVERAGE - CLEAN VIEW

IDV26	Width	Height
126CV1*	$34^{1}/2''$	22"
126CV2*	411/2"	25 ¹ /2"
126CV3*	34"	22"
126CVPF1*	$34^{1}/2''$	25"
126CVPF2*	411/2"	$32^{3}/8$ "
126CV1DS*	34 ¹ /2"	22"

^{*}Back Frame Dimension of Clean View Kit



IDV26RL Traditional Brick Liner

LOGF27 Fibre Split Oak Logo Set



IDV26N Direct Vent Insert – Natural Gas, LOGF27 Log Set, I26CVPF2BL Clean View Picture Frame – Black, IDV26RL Refractory Brick Liner.

BLACK

- IDV26N Direct Vent Insert Natural Gas, I26CV2BL Clean View Kit
 Black, LOGF27 Log Set, IDV26RL Refractory Brick Liner.
- 3. IDV26N Direct Vent Insert Natural Gas, I26CVPF1BL Clean View Picture Frame Black, LOGF27 Log Set, IDV26PRL Porcelain Reflective Liner.
- 4. IDV26N Direct Vent Insert Natural Gas, I26CV1BL Clean View Kit Black, I26S1BL Surround Black, LOGF27 Log Set, IDV26RL Refractory Brick Liner.

2340 Logan Avenue Winnipeg, Manitoba, Canada R2R 2V3 Phone: (204) 632-1962 Fax: (204) 632-1960

www.kingsmanfireplaces.com

IDV26

DIRECT VENT GAS FIREPLACE INSERT





*Components may have to be ordered separately to create a complete unit. Discuss with your local Kingsman dealer for clarification. Kingsman Fireplaces maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation. Certification: Certified for Canada/USA as a Vented Cass Fireplace Heater ANSI 221.88-2014. CSA 2.33-2014. CGA 2.17-M91 (R2009). Printed in Canada 03/18 – B076

