

Quality Acrylic Bath

I C S Quality Acrylic Baths

Custom Manufacturing

www.ICSQUALITYBATHS.com

Clearwater, Florida

813-671-9505

**Builder Series Bath - 504 HRD
CR 60 x 22 x 20**

Model: Specifications

6 flow adjustable and directional jets


1 pump (1.25 BHP)

7.2Amps


(1) on/off Air Switch

Silent air induction

Operating Gallons - 50 gal. reg. usage



(Cutout is 1" LESS than outside dimensions.)




60"	A	Length
60"	B	Width Flat 20"
22"	C	Height
46"	D	Back Corner to Center of Drain
5"	E	Edge of Tub to Center of Waste
17"	F	Base of Tub to Center of Overflow
18"	G	Bottom of Lip to Floor
22"	H	Right/Left Side of Tub
53.5"	I	Front of Tub

Inside Bottom Dimension 40"L x 27"W (+/- 1/2")



**60"x60"x22"
Shipping weight - 140lbs**

Model: Pump Locations



Stand Facing Tub

THE TOTALLY INSULATED BATH...
Each Premium Bath is surrounded by high density urethane foam insulation.

THE INSULATION EFFECTIVELY...
Retains Heat
Eliminates Motor Noise
Eliminates In-Line Heater
Protects Plumbing & Bath Shell

Optional Features Available:

- * Tri-ssage Control with "3" Distinct Flow Rates
- * Mood or LED Light
- * Contoured Neck Support Pillow or Neck Jet Pillow
- * Polished Brass, Polished Chrome or Brushed Nickel Trim
- * Whirly Triple Spinning Jets