

Reliable skidding winch engineering with over 45-years experience

Profitable choice - since 1962








501

- The automatic overrunning brake device guarantees a very smooth pull-out of the cable and prevents run on
- A high pivoted cable entry guarantees optimum spooling into the cable drum
- Decades experience in all weather conditions



The FARMI 501 winch (with 11,000 lbs pull for tractors from 35 HP and up) is manufactured with an integrated butt plate and a vertically adjustable lower cable pulley: a rugged and stable winch.



Power shaft in the center line of the winch

FARMI Skidding winches: Technical information

		290	351P	501
We reserve the right to make changes.	Pulling force, max. lbs	6,400	7,700	11,000
	Cable capacity	ø 5/16", 262' ø 3/8", 180'	ø 5/16 ", 295 ' ø 3/8 ", 196 '	ø 5/16 ", 327 ' ø 3/8 ", 262 ' ø 1/2 ", 196 '
	Feed-in speed 350 rpm, feet/s 540 rpm, feet/s	.6 - 3.2	1 - 2.8 1.6 - 4.2	1-3 1.6 - 4.6
	Mechanical plate coupling	yes	yes	yes
	Required power, min. hp	from 15	from 15	from 35
	Automatic drum brake	yes	yes	yes
	Weight without the cable, lbs	330	374	551
	Three-point mounting	Cat. I	Cat. I and Cat. II	Cat. I and Cat. II
	Dozer blade and notched beam	yes	yes	yes
	Protective screen	standard	standard	standard
	Lower guide pulley	no	yes	yes
	Holders for long chains	yes	yes	yes
	Tool box	no	no	yes





Farmi Forest Corporation Ahmolantie 6 FI-74510 lisalmi FINLAND Tel. +358 17 832 41 Fax +358 17 382 4372 info@farmiforest.fi Northeast Implement 460 Halsey Valley Road Spencer, NY 14883 Tel. 607-589-6160 Tel. 888-589-6160 Fax 607-589-4026 www.northeastimplement.com

www.farmiforest.fi