

W.L.S. Coatings, Inc.
1680 Miller Ave. Los Angeles CA. 90063
(310) 538-2155 / FAX (310) 329-2005

PRODUCTS: WLS 100-39

DESCRIPTION: MODIFIED VINYL, SINGLE COMPONENT NEUTRAL PINHOLE FILLER.

USE: FOR INDUSTRIAL USE ONLY. NOT INTENDED FOR HOME USE.

This product has excellent filling properties and is intended to be used as Pin hole Filler for plastic and metal substrates. It exhibits very good sandability and will provide excellent chemical, solvent and water resistance. It has excellent adhesion and is intended to be used over metals, wood, fiberglass laminates, polyethylene and other other plastics substrates. Meets McDonnell Douglas Corp. DPM specification No.6200.

TECHNICAL DATA:

NON-VOLATILE (WEIGHT): 75%

NON-VOLATILE (VOLUME): 54%

DRYING TIME@70 F. AND 40% RELATIVE HUMIDITY:

SET TO TOUCH: 15 minutes

DRY HARD: 2 Hours

SURFACE PREPARATION:

Surfaces to be filled should be dry and free of dirt, grease, oil, mill scales, Rusts and other foreign contaminants. Solvent clean with Methyl Ethyl Ketone or or other appropriate solvents.

APPLICATION:

Filler may be applied using squeegee, gloved hands or putty knife. Pin holes will be filled more efficiently using a squeegee. Larger holes should be filled using gloved hands or putty knife.

WLS 100-39 Page 2

STORAGE STABILITY: 12 MONTHS MINIMUM AT 70 F.

PRECAUTIONS:

HARMFUL OR FATAL IF SWALLOWED.

**FLAMMABLE, KEEP AWAY FROM HEAT, SPARKS
AND OPEN FLAME**

EYE IRRITANT.

**AVOID PROLONGED SKIN CONTACT AND
EXCESSIVE INHALATION OF VAPORS. In case of eye
contact, flush repeatedly with soap and water. If
swallowed do not induce vomiting. Call a Physician
immediately.**

USE WITH ADEQUATE VENTILATION

KEEP OUT OF REACH OF CHILDREN