



Agility water-cooled chillers

Compact chillers that fit your needs

Compact

The addition of the Agility™ chiller to the Trane portfolio provides the next step in compact chillers. Providing best-in-class size, the Agility chiller portfolio provides an optimized footprint that minimizes installation costs making it the best choice for existing building applications. The Agility chiller fits through a standard double door (72 inch x 80 inch) fully assembled, and can be easily separated into two sections that fit through a single door (36 inch x 80 inch).

Economical

The Agility chiller delivers the best balance of size and efficiency, all while helping to keep installation costs low. Leveraging oil-free, magnetic bearings with optimized compressor speeds and the latest Trane proprietary (CHIL™) heat exchanger designs, these technologies enable a smaller footprint while delivering Integrated Part Load Values (IPLV) over 40 percent better than the ASHRAE® 90.1-2016 plus high full-load values. The Agility chiller's compact size will keep installation costs low, and its efficiency will help reduce electrical consumption (kWh or part load) as well as demand charges (kWh or high load) contributing to low operating expenses.

Reliable

The Agility chiller has legendary Trane reliability designed in from the start. It utilizes a two-stage, semi-hermetic centrifugal compressor with a permanent magnet, refrigerant-cooled motor delivering efficient, stable operation across a wide operating map. Couple this with Trane AdaptiView™ unit controls and customers will enjoy maximum flexibility to meet their applications' needs. Trane controls also allow for remote connectivity, enabling optimum unit performance to deliver reliable and efficient operation. All of this is backed by factory available extended warranties with coverage up to and including 10 years for parts, labor and refrigerant — truly covering the whole chiller.

Simplex Chiller Model HDWA

175 to 425 ton – 60 Hz, 50 Hz
using either R-513A or R-134a



EcoWise™



The Agility water-cooled chillers with R-513A are part of the Ingersoll Rand EcoWise portfolio of products designed to lower environmental impact by using next-generation, low global warming potential (GWP) refrigerants without compromising performance and reliability.

Next-Generation Refrigerant


The Agility chiller's design is optimized with the next-generation, low-GWP refrigerant R-513A in mind. This refrigerant provides a 55 percent drop in GWP over R-134a helping customers meet sustainability goals by reducing the impact to the environment. The Agility chiller can also be selected with R-134a refrigerant.




Base Unit
(Assembled)



Cont/Cond
Section



Comp/Evap
Section



Unit Configuration

Compressor	Shell Config (EVAP/COND)
200	020/020
300	020/020
300	040/040
400	040/040

Base Unit Dimensions (Assembled)


Length		Width		Height	
in	mm	in	mm	in	mm
129.9	3300	67.4	1713	72.2	1833
129.9	3300	67.4	1713	72.2	1833
129.9	3300	70.7	1795	78.0	1981
129.9	3300	70.7	1795	78.0	1981

Cont/Cond Section

Width (W ₁)		Height (H ₁)	
in	mm	in	mm
33.8	858	72.2	1833
33.8	858	72.2	1833
33.8	859	78.0	1981
33.8	859	78.0	1981

Comp/Evap Section

Width (W ₁)		Height (H ₁)	
in	mm	in	mm
34.9	886	63.4	1610
35.2	893	68.4	1738
35.2	893	68.4	1738
35.2	893	68.4	1738



Unit Voltages

- 460/480V 60 Hz
- 575/600V 60 Hz
- 208/230V 60 Hz

Unit Configuration

Compressor	Shell Config (EVAP/COND)
200	020/020
300	040/040
400	040/040

Space Envelope

Length (E _L)		Width (E _W)		Height (E _H)	
in	mm	in	mm	in	mm
300.8	7641	139.4	3553	108.2	2753
300.8	7641	139.4	3553	108.2	2753
300.8	7641	142.7	3635	114.0	2901
300.8	7641	142.7	3635	114.0	2901

Unit Clearance

Tube Pull (C _{L1})		Non-Tube Pull (C _{L2})		Height (H _C)	
in	mm	in	mm	in	mm
129.9	3300	41.0	1041	36.0	920
129.9	3300	41.0	1041	36.0	920
129.9	3300	41.0	1041	36.0	920
129.9	3300	41.0	1041	36.0	2901

Dimensions do not include waterboxes, hinges or other unit-mounted options that may affect unit size.

1. C_{L1} can be at either end of the machine and is required for tube pull clearance.
2. C_{L2} is always at the opposite end of the machine from C_{L1} and is required for service clearance.

Contact your Trane representative for more information.

LET'S GO BEYOND™



Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$13 billion global business committed to a world of sustainable progress and enduring results.



Trane, the Circle Logo, Let's Go Beyond, Agility, CHIL, EcoWise and AdaptiView are trademarks of Trane in the United States and other countries. ASHRAE is a registered service mark of the American Society of Heating, Refrigerating, and Air-Conditioning Engineers, Inc. All trademarks referenced in this document are the trademarks of their respective owners.

ingersollrand.com

We are committed to using environmentally conscious print practices.

©2018 Ingersoll Rand. CTV-SLB064-EN
January 23, 2018