

Model: AJ2444Z-FZ3Y

Product Description

Type: Reciprocating Compressors
Application: LBP - Low Back Pressure
ProductDescription: R-404A
Voltage/Frequency: 220-240V ~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					

General

Evaporating Temp. Range: -40°C to -12.2°C (-40°F to 10°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 22
Weight Unit of Measure: KG
Displacement (cc): 34.45
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 475

Electrical

Voltage Range (50 Hz): 198-253
Voltage Range (60 Hz):
Locked Rotor Amps (LRA): 40
Rated Load Amps (RLA 50 Hz): 5.7
Rated Load Amps (RLA 60 Hz): 0
Max. Continuous Current (MCC in Amps): 10
Motor Resistance (Ohm) - Main: 1.6
Motor Resistance (Ohm) - Start: 6.5
Motor Type: CSR
Overload Type:
Relay Type:

Agency Approval