

SPEC SHEET GUIDELINE

Bonita Pines recommended Sound proofing for the 2nd & 3rd Floor Units -
Bonita Pines have a 6” Concrete slab with no ceiling

Sound proofing underlayment	IIC rating	STC rating			Available for Purchase
Carpet & Padding - Heavier density foam padding is recommended for better soundproofing	N/A	N/A	7/16” or 1/2” foam padding with heavier density ratings is Recommended by the Board - Will meet soundproofing standards		
Proflex Super Sim-90 - Ceramic Tile/Stone/ Floating Laminate -Can not be used on a glue down application.	50	52	Meets Florida Code and Recommended by Board Research - Can be used in whole unit	www.proflex.us	Shoreline Flooring Supplies
Proflex LV-200 - Laminate Wood-glued or floating application	54	50	Meets Florida Code and Recommended by Board Research - Can be used in whole unit	www.proflex.us	Shoreline Flooring Supplies
- Luxury Vinyl Tiles & Planks-glued or floating application only	56	52	Meets Florida Code and Recommended by Board Research - Can be used in whole unit	www.proflex.us	Shoreline Flooring Supplies
Eco Ultimate Silencer - Laminate/Hardwood	52	51	Meets Florida Code and Recommended by Board Research - Can be used in whole unit	www.foamproducts.com	Shoreline Flooring Supplies
Eco-Ultra Quiet Premium Acoustical Underlayment - Laminate/Hardwood	52	51	Meets Florida Code and Recommended by Board Research - Can be used in whole unit	Floor & Decor Website	Floor & Decor
Proflex MSC 90 - Don't know rating for 6” Deck - they just have ratings on a 8” Deck	NOT TO CODE FOR 6” CONCRETE SLAB W/NO CEILING	NOT TO CODE FOR 6” CONCRETE SLAB W/NO CEILING	CAN ONLY BE USED IN BATHROOMS & KITCHEN - CAN NOT BE USED ANYWHERE WITHOUT A DROPPED CEILING	www.proflex.us	Lowes or Shoreline Flooring

PLEASE NOTE: If your contractor recommends a different product for sound control, an acoustical Data Report must be provided with the Architectural Improvement Application to verify that Florida State IIC Code is met with a 6” concrete slab with NO ceiling.

PLEASE NOTE: The Board requires DuraRock to be hung behind all new tile work in shower area of Bathrooms.