



Ultraleather® | Original



Ultraleather® | Original



291-2509 Poseidon



291-0001 White



291-5668 Silver Pearl




291-5666 Dove Grey



291-2508 Rain Dance




291-5806 Schooner



291-5714 Ice



291-5040 Elephant



291-5708 Granite



291-5763 Charcoal



291-5607 Raven Wing



291-5200 Citrus



291-5250 Sassy



291-8233 Autumn Leaf



291-1347 Poppy




291-1176 Red



291-7213 Desert Rose



291-6588 Salmon



291-1334 Toro



291-1311 Brick



291-1312 Chianti



291-7214 Boysenberry



291-6580 Sorbet



291-3469 Garnet



291-9385 Plum




291-9380 Dusk



291-2685 Bayou



291-2478 Diplomat Blue



291-2556 Admiral



291-2555 Nile



291-2551 Baltic



291-2533 Cyan



291-2527 Lagoon



291-2507 St. John



291-2552 Riviera




291-4314 Herbal Mist




291-4430 Eucalyptus



291-4460 Parrot




291-4454 Sonora



291-4313 Sweetgrass



291-4351 Shetland



291-8243 Apricot



291-8219 Adobe




291-3612 Curry



291-3610 Hide



291-3205 Hot Chocolate



291-3851 Chamois



291-3778 Pecan




291-3779 Taupe



291-3777 Walnut



291-3666 Fudge



291-3850 Sand




291-3609 Buff



291-3926 Cashmere



291-3183 Pine Cone



291-3523 Cave




291-3720 Light Oyster



291-3719 Champagne




291-3601 Doe



291-3729 Tan



291-1256 Papyrus



291-3599 Almond




291-3455 Milkweed




291-5684 Arctic



291-5676 Pelican



291-3602 Stone



291-5805 Ermine



291-3700 Ivory



Abrasion Plus



Custom

Ultraleather® | Original

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface

100% Reinforced Rayon Backing

Weight:

Approx. 9.7 oz. Per Square Yard

Approx. 330 Grams Per Square Metre

Thickness:

Approx. 1.0 Millimetres

Width:

54 Inches / 137 Centimetres

Performance

Abrasion:

ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)*

BS 2543 / 180,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

14+ Weeks

ASTM D3690-02 Sect. 6.11 (Hydrolytic Stability)

ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating:

ASTM D751

Tear Strength:

ASTM D2261

Breaking Strength:

ASTM D5034

Colorfastness

Light Fastness:

AATCC 16.3, 200 Hours, Grade 4-5

Crocking:

AATCC 8, Class 5 Wet & Dry

Flammability

F/R Rating:

- ASTM E84 (Adhered) - Class A
- CA TB 117-2013 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

Other Tests*:

- ASTM E84 (Unadhered)
- BS 5852 PT 0, 1 & 5 (Crib 5)
- BS 5867 Part 2 Type B
- BS 7175
- California Technical Bulletin 133
- FAR Specifications
- IMO A.652 (16)
- NFPA 701

*These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under these fire test conditions.

Earth Friendly

• GREENGUARD Gold Certified

- Meets stringent chemical emission limits for various VOCs (ex. Formaldehyde)
- Promotes healthier indoor air quality
- Contributes towards satisfying credits under LEED® and BIFMA
- Compliant with California Section 01350

• Meets Healthier Hospitals Safer Chemicals Challenge, V2.0

- Compliant with Prop 65
- No Bisphenol A (BPA)
- No Conflict Minerals
- No Flame Retardants (Halogenated, Brominated: ex. PBDEs)
- No Heavy Metal Stabilizers
- No PFCs (Perfluorinated Chemicals)
- No Plasticizer Phthalates
- No POPs (Persistent Organic Pollutants)
- No PVC (Polyvinyl Chloride)
- No toxic by-products
- Over 99% of solvents recaptured and recycled

For more information on our fabrics, cleaning and care instructions, please visit our website.



PRODUCT
CERTIFIED FOR
LOW CHEMICAL
EMISSIONS:
UL.COM/SGG
UL 2818



A PRACTICE GREENHEALTH PROGRAM

ultrafabricsinc.com

Ultrafabrics® and logo, and Ultraleather® are trademarks of Ultrafabrics Inc. Made in Japan.

3/18

