



Ultraleather® | Pro



EPA-registered antimicrobial protection • Ink and denim resistant

Ultraleather® | Pro



554-3087 Woodcres



554-0008 White Wash



554-5648 Cloud



554-5733 Mortar



554-5626 Char



554-5618 Dark Knight



554-3811 Swan



554-3803 Parfait



554-3352 Shore




554-3595 Cork



554-3444 Toasted Bagel




554-5216 Butterfly




554-5241 Butternut



554-8229 Campfire



554-1329 Rhubarb



554-1357 Cranberry



554-5649 Ember



554-7200 Blush



554-3209 Cougar



554-3214 Chestnut



554-3376 Dark Chocolate



554-4478 Sea Mist



554-3353 Tundra




554-3087 Woodcres



554-4443 Laurel



554-4453 Persian Green



554-2661 Blue Bird




554-2522 Capri



554-4530 Coastal



554-9336 Aubergine



554-9395 Violet



554-2530 Sky



554-2711 Blueberry



554-2547 Sailor



Ink & Stain
Resist



Abrasion Plus



Antimicrobial



Custom

Ultraleather® | Pro

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface

100% Reinforced Rayon Backing

Weight:

Approx. 9.7 oz. Per Square Yard

Approx. 330 Grams Per Square Metre

Thickness:

Approx. 0.95 Millimetres

Width:

54 Inches / 137 Centimetres

Performance

Abrasion:

ASTM D4157 / 500,000 Double Rubs (Wyzenbeek)*

BS 2543 / 200,000 Rubs (Martindale)*

*meets or exceeds

Hydrolysis:

14+ Weeks

ASTM D3690-02 Sect. 6.11 (Hydrolytic Stability)

ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating:

ASTM D751

Tear Strength:

ASTM D2261

Breaking Strength:

ASTM D5034

Antimicrobial:

ASTM E2180

Colorfastness

Light Fastness:

AATCC 16.3, 200 Hours, Grade 4-5

Crocking:

AATCC 8, Class 5 Wet & Dry

Flammability

F/R Rating:

- ASTM E84 (Adhered) - Class A
- CA TB 117-2013 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

Other Tests*:

- ASTM E84 (Unadhered)
- BS 5852 PT 0, 1 & 5 (Crib 5)
- BS 5867 Part 2 Type B
- BS 7175
- California Technical Bulletin 133
- FAR Specifications
- IMO A.652 (16)
- NFPA 701

*These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under these fire test conditions.

Earth Friendly

• GREENGUARD Certified

- Meets stringent chemical emission limits for various VOCs (ex. Formaldehyde)
- Promotes healthier indoor air quality
- Contributes towards satisfying credits under LEED® and BIFMA

- Compliant with Prop 65
- Less than 100 ppm of EPA-registered antimicrobial treatment
 - No Triclocarban or Triclosan
- No Bisphenol A (BPA)
- No Conflict Minerals
- No Flame Retardants (Halogenated, Brominated: ex. PBDEs)
- No Heavy Metal Stabilizers
- No Plasticizer Phthalates
- No POPs (Persistent Organic Pollutants)
- No PVC (Polyvinyl Chloride)
- No toxic by-products
- Over 99% of solvents recaptured and recycled

Ultraleather® | Pro resists:



Ballpoint ink



Betadine



Blood



Denim*



Mustard/ketchup



Red Wine

*Removal of denim dye may vary depending on the period of time the stain sets in. While Pro offers excellent protection, full removal is not guaranteed.

For more information on our fabrics, cleaning and care instructions, please visit our website.



PRODUCT
CERTIFIED FOR
LOW CHEMICAL
EMISSIONS:
UL.COM/GG
UL 2818

Ultrafabrics® and logo, and Ultraleather® are trademarks of Ultrafabrics Inc. Made in Japan.

ultrafabricsinc.com



11/17